



soundskins®

Bronco Kit Door Installation Instructions

Tools needed for installation:

- 7mm socket
- Socket extension
- Panel /trim tool
- Roller
- Microfiber cloth
- Acetone or cleaning solution

Scan this code to watch the full instructional video!



1. Start by locating the fastening hardware on the door panels. There will be one behind the door handle under a plastic cover, one behind the door grab handle that you will have to pop out to reveal, and 2 at the bottom right corner of the door panels. Take a 7 mm socket and remove. Then, use a panel tool to pry the panel off the door, start from the bottom right corner. Be sure not to break any clips or mounting hardware.



2. Pull the door panel away slowly. There will be 2 plug clips that will need to be released as well as a wire plug to disconnect. Set the door panel aside and unhook all plugs, remove the vapor barrier, and clean the car metal surface using a microfiber cloth and Acetone or other cleaning solution. The point is to get the surface clean to ensure material glue contact.



3. Now, apply the door pieces. Peel off the backing paper starting at the top, tack the piece onto the door and work your way down, pressing down the material and pulling down the backing paper more as you go along. Feed the harnesses through the proper holes and ensure everything is aligned before pressing the entire piece down. Repeat steps 1-3 for all doors. Then replace your door panels and reconnect the wires and enjoy your quiet new ride!

Soundskins USA

13452 Alondra Blvd, Cerritos, CA 90703

Phone: 877.211.5597

Email: team@soundskinsglobal.com

www.SoundSkinsGlobal.com