Residential Range

Flood Lights

Flood Light with IP Camera

Product Code	LED's	Battery	Solar Panel	IP Rating	Lumens
SLDFL007 /BLK-WW	10W LED Panel (WW)	1 x 3.7v 8800mAh Lithium	20W Separate Polycrystalline	65	1000 @ 1m
SLDFL007 /WHT-WW	10W LED Panel (WW)	1 x 3.7v 8800mAh Lithium	20W Separate Polycrystalline	65	1000 @ 1m

Features:

- 120º Rotatable Design
- Microwave Motion Sensor Range: 10m
- Concealed installation
- Internet Protocol (IP) with Wi-Fi
- 3 Mega Pixel Camera
- 24/7 Recording Capability
- In-House Storage → 32GB TF Card
- Smart Phone Connectivity via APP

1 Year Warranty!

3 Modes of Operation:

- Mode 1: Operate at 25% brightness until motion is detected, then run for approx. 30 secs at 100% brightness or until no further movement is detected
- Mode 2: OFF until motion is detected, then run for approx. 30 secs at 100% or until no further movement is detected.
- Mode 3: Operate at 50% brightness from dusk to dawn or until battery is discharged (Sensor Bypass Mode)

Packaged Fitting Weight & Dimensions

W: 2.9kg

D: 36cm x 36cm x 15cm





