

INSTRUCTION GUIDE

Commercial Pillar

Model No. SLDPIL1012/BLK

INSTALLATION METHOD

- 1. Remove contents from packaging
- 2. Flip fitting onto its head so that the solar panel is completely covered
- Locate "ON/OFF" switch by pressing the button that is situated on the bottom of the pillar base (FIGURE 1)



FIGURE 1

- 4. Temporarily cover solar panel with solid surface for testing purposes only Light should illuminate
- 5. Remove the solid surface & the light will turn "OFF".
- 6. The light is now in Dusk to Dawn Mode and ready to use

IMPORTANT NOTES

- Please ensure you place your solar panel in a location where it can achieve a minimum of 6HRS DIRECT SUNLIGHT
- Be aware that with overcast/cloudy days, the solar panel will still charge. However, not as efficiently as a sunny day, so the battery may not reach full capacity. Therefore turning off earlier than specified.
- It's best not to install these lights underneath a street light, porch light etc. because this may stop the automatic daynight sensor triggering and result in your lights not turning on

TROUBLE SHOOTING

Phenomenon	Cause	Inspection Method	Solution
Light won't turn on	Switch hasn't been turned on	Detect what position the switch is in	Turn the switch on
	Battery has run out	Long rainy days or installation site doesn't provide enough light	Charge the light in direct sunlight for 1-2 days then check again
Short lighting time	Low Battery	1. Bad installation site for the light 2. Dust and leaves are covering the panel 3. Long period of rainy days	1. Charge the battery in direct sunlight for 1-2 days with switch off, then check again 2. Clean the solar panel
	Battery Failure	1. Access the light and check if the battery has moved or if it has been damaged 2. Battery has matured and requires replacing	Contact us to replace your battery

Customer Service Number: 1300 135 911 www.solarlightingdirect.com.au