

INSTRUCTION GUIDE

Commercial Park Light

Model No.SLDPKL10W

INSTALLATION METHOD

Remove contents from packaging

Please note: the light has no "ON/OFF" button, this is controlled via the supplied remote

- 2. Place your light in a location where it will receive maximum direct sunlight (with the light programmed in the "OFF" position) for 2 days before installation
- 3. Turn the light "ON" and adjust light setting to your preference (Please refer to 'UNDERSTANDING YOUR REMOTE' for this step)
- 4. Temporarily cover solar panel with solid surface for testing purposes only - Light should illuminate
- 5. Remove the solid surface & the light will turn "OFF". The light is now in Dusk to Dawn Mode

UNDERSTANDING YOUR REMOTE



Master OFF Button, Returns all settings to factory default



100% Brightness



50% Brightness



AUTO Dusk to Dawn Mode



Brightness **UP**



Brightness **DOWN**



Lighting Time (3, 5 or 8 hrs)



Colour temperature selector (Daylight, Warm White & Cool White)



Batteries not included 2x AAA batteries required

IMPORTANT NOTES

- Please ensure you place your solar panel in a location where it can achieve a minimum of 6HRS DIRECT **SUNLIGHT**
- Be aware that on overcast/cloudy days, the solar panel will still charge. However, not as efficiently as a sunny day, so the battery may not reach full capacity. Therefore, your light may turn off earlier than specified
- It's best not to install the fitting underneath a street light, porch light etc. because this may stop the automatic daynight sensor triggering and result in your lights not turning on

TROUBLE SHOOTING

Phenome non	Cause	Inspection Method	Solution
Light won't turn on	Switch hasn't been turned on	Determine what position the switch is in	Turn the switch on
	Battery has run flat	Period of rainy or cloudy weather or installation site doesn't provide enough direct sunlight	Charge the light in direct sunlight for 1-2 days then check again
The light only stays on for a short amount of time	Low Battery	1. Bad installation site for the solar panel 2. Dust or leaves are covering the panel 3. Long period of overcast weather	1. Charge the battery in direct sunlight for 1-2 days with the switch off, then check again 2. Clean the solar panel
	Battery Failure	Access the light and & replace battery Battery has matured	Contact SLD Customer Service to buy new batteries