

Wet-Location Adjustable Emergency Lights

ESW-EWL-TFX-2 wet-location adjustable emergency lights offer fully adjustable lamp heads, along with waterproof construction ideal for wet-location applications and resistant to corrosive atmospheres, non-hazardous dust environment, frequent hose-downs, water spray and splashing water.

ESW-EWL-TFX-2







Features


- Dual-voltage input 120V/277V
- Maintenance-free sealed lead-acid battery (ESW-EWL-TFX-2) and nickel-cadmium battery (ESW-EWL-TFX-2)
- Remote-capable standard up to 14.4W (ESW-EWL-TFX-2) and 4.4W • (ESW-EWL-TFX-2)
- Sealed and gasketed housing •
- Corrosion- and impact-resistant thermoplastic housing •
- ESW-EWL-TFX-2-two factory-installed fully adjustable 6V 7.2W lamp heads •
- ESW-EWL-TFX-2—two factory-installed fully adjustable 15 LED lamp heads •
- Temp rating: 1940° wet
- UL 924 Listed for wet location
- CSA Listed (ESW-EWL-TFX-2)

Dimensions

ESW-EWL-TFX-2







Ordering Information

Series	Options	Example Cat #
ESW-EWL-TFX-2	Blank = Standard	ESW-EWL-TFX-2
ESW-EWL-TFX-2	Blank = Standard RC = Remote Capable	ESW-EWL-TFX-2