BPL101-50

Photoluminescent Exit Sign



Two self-adhesive directional indicators are supplied with each sign. Small dots are also provided to the left of the letter E and to the right of the letter T for easy alignment.

Non-electric
Non-radioactive
Non-hazardous
No expiration date
Energy efficient
LEED points qualified
Zero annual operating expense
No batteries
No bulbs
Low maintenance
100% reliable
High or low level
Simple installation
25+ year life expectancy

Red Letters



Green Letters



The BPL 101-50 UL 924 Listed EXIT signs are available with durable anodized aluminum frames. The frames have been designed for ceiling, T-bar, flag, or surface mount applications and can accomodate single or double face signs. We stock our clear anodized aluminum frames. All other colored frames are special order, so please allow extra time for delivery. Additional custom frame colors are available upon request. Two directional chevrons and all mounting hardware are included with each sign. Designed for maximum durability, the BPL101-50 Series Photoluminescent Exit Sign is Constructed out of rigid PVC. Ideal for high and low level applications. Easy peel and stick directional chevrons. UL 924 Listed with four external charging light sources: fluorescent, metal halide, LED, and mercury vapor.

specificationscations

BPL101-50

Letter Size: 1" Stroke with 7" Height

Letter Color: Green or Red Background: Photoluminescent

Directional: Two directional chevrons included for field application.

Viewing Distance: 50 Feet Life Expectancy: 25+ Years

Applications: High and Low Level, indoor use only.

Installation: Minimum 5 foot-candle (54 lux) external unfiltered fluorescent, metal halide or mercury vapor illumination

must be present on the sign face at all times of building

occupancy.

Sign Substrate: Photoluminescent self-extinguishing PVC.

Frame Substrate: Aluminum

Features: Non-electrical, non-radioactive, explosion proof,

UV-stable, durable, minimal installation and

maintenance expense

Compliance: UL 924 Listed, Energy Star Listed, Meets NFPA 101 Life

Safety Code, NFPA 5000, JCAHO & OSHA, ICC - IBC, ICBO - UBC, BOCA - NBC, SBCCI - SBC, 1/UFC, CA Bldg. Code,

ASTM 2072, and CSFM Listed

Warranty: 15-year limited warranty to the original customer covering


any defects in material or workmanship.

Catalog Model #	Mounting	Frame Color	Number of Faces	Letter Color
BPL10150F	C - Ceiling F - Flag S - Surface T - T-Bar U - Universal W- Window	A - Anodized Aluminum B - Anodized Bronze BL- Anodized Black G - Anodized Gold W - Powder Coat White	S - Single* D - Double	G - Green R - Red
,			*Back plates available for an additional charge.	

Frame Colors Aluminum Black Bronze Gold White Red Green

Ceiling Mount 57 Name (uplan Name) Designer 1/ red (2) Milleans) 15 75" 15 75"

T-Bar Ceiling Mount



Surface Mount



Flag Mount



Low Location Window Mount

