


GM50 Series 20 Year Limited Warranty



The ultimate impact resistant, metal constructed UL 924 Listed





Lights off



Easy to remove chevrons

Non-electric
Non-radioactive
Non-hazardous
No expiration date
Energy efficient
LEED points qualified
Zero annual operating expense
No batteries
No bulbs
Low maintenance
100% reliable
High or low level
Simple installation
25+ year life expectancy







Designed for maximum durability, the Glow Maxx 50 Photoluminescent Series Exit Sign is constructed using a steel stencil face plate with rigid photoluminescent insert. Ideal for high and low level applications. Easy pop out directional chevrons. UL 924 Listed with three external charging light sources: fluorescent, metal halide, and mercury vapor.

specifications

Overall Size:

15.5"W x 8.5"H x .25" Depth

Letter Size:

1" Stoke, 7"Height

Weight:

3 lbs

Construction:

Steel Stencil Face plate with rigid photoluminescent insert

Illumination:

Strontium Oxide Aluminate Photoluminescent pigment laminated

to rigid PVC

Face Plate Colors: Letter Color:

Black, Green, Red, Silver and White Photoluminescent, Green Illuminating

Directional:

Pop-out chevron arrows

Initial Activation:

Based on UL 924 Standards, requires minimum 5 foot-candles (54 lux) of unfiltered fluorescent, metal halide or mercury vapor

lighting for 60 minutes.

Installation:

Install photoluminescent Exit signs only in locations where an external illumination source is present, is deemed reliable, and is supplied by a circuit not controlled by automatic timers or sensors and where controls are accessible only to authorized personnel. This reliable external illumination source is to be energized at all

times during building occpancy.

Viewing Distance:

50 Feet - Sign will remain visible and legible in total darkness to observers standing 50 feet away from the sign for at least 90

minutes after all light has been extinguished.

Life Expectancey:

25+ years

Applications:

High and low level, indoor use only

Approvals:

UL 924 Listed, Meets NFPA 101 Life Safety Code, NFPA 5000, JCAHO & OSHA, ICC, - IBC, ICBO - UBC, BOCA - NBC, SBCCI -

SBC, 1/UFC, CA Bldg. Code, ASTM 2072 and CSFM Listed

Product Care:

Periodically clean the sign face with a damp cloth, and conduct periodic inspections to ensure the sign is clear and visible.

Warranty:

20 year limited warranty from the date of shipment against defects in workmanship and materials to the original customer

Mounting Options Surface • Ceiling • Flag • T-Bar



Front with Universal Bracket



Back, 10-24 X 5/16 Set Screw Location



Front Surface Mount, #8-1 1/2 Phillips Pan-Head Screen

Description Item No.'s

black, wall mount exit sign BPLGM50WB black, single-sided sign w/bracket BPLGM50SB black, double-sided sign w/bracket BPLGM50DB black, single-sided sign w/T-bar bracket BPLGM50STB black, double-sided sign w/T-bar bracket BPLGM50DTB silver, wall mount exit sign BPLGM50WS silver, single-sided sign w/bracket BPLGM50SS silver, double-sided sign w/bracket BPLGM50DS silver, single-sided sign w/T-bar bracket BPLGM50STS silver, double-sided sign w/T-bar bracket BPLGM50DTS

red, wall mount exit sign red, single-sided sign w/bracket red, double-sided sign w/bracket red, single-sided sign w/T-bar bracket red, double-sided sign w/T-bar bracket green, wall mount exit sign green, single-sided sign w/bracket green, double-sided sign w/bracket green, single-sided sign w/T-bar bracket BPLGM50STG green, single-sided sign w/T-bar bracket BPLGM50STG

white, wall mount exit sign white, single-sided sign w/bracket white, double-sided sign w/bracket white, single-sided sign w/T-bar bracket white, double-sided sign w/T-bar bracket BPLGM50DTW

BPLGM50WR BPLGM50SR BPLGM50DR BPLGM50STR BPLGM50DTR BPLGM50WG BPLGM50SG BPLGM50DG BPLGM50WW BPLGM50SW

8.5 BPLGM50DW BPLGM50STW

