

Project:	
Type :	
Catalog #:	



ILLUMINATION

- Ultra-bright, energy efficient, long-life white LED lamp heads.
- 1.0 watt (1 LED x 1.0 watt) per head.
- Unique all-inclusive lamp, reflector, and lens assembly.
- Adjustable LED lamp heads provide up to 50-ft center-tocenter spacing with a 3-ft path of egress at 12-ft mounting height.

ELECTRICAL

- Universal 120-277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable nickel metal hydride battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

 Bar hangers included are compatible with drywall or drop ceiling mount installations

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, impact-resistant, thermoplastic in white or black finish.
- Injection-molded, engineering grade, 5VA flame retardant, thermoplastic oval and rectangle trim plates in white or black finish included.




OPTIONS

• SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

WARRANTY / LISTING

- Five-year warranty on all electronics and housing. Battery pro rated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations.(10°C 50°C)



Sample Part Number: RM-EM-LP

ORDERING INFORMATION

MODEL	HOUSING COLOR		OPTIONS	
RM-EM-LP	W	White	SDT	Self-Diagnostics
	В	Black		