

## LED FLAT PANEL RETROFIT KIT

### FPR SERIES



ETL CLASSIFIED



### PRODUCT DESCRIPTION:

The Flat Panel Retrofit Kit is the easy and cost-effective solution to upgrade fluorescent troffers to LED. The kit utilizes the existing troffer housing, thereby reducing labor time and expense since installation can be performed from below the ceiling. An existing troffer can be retrofitted in just minutes!

The kit's edge lit LED light source delivers uniform illumination with minimal glare, and creates a clean aesthetic that is perfect for offices, retail, health care, educational, hospitality and other commercial facilities.

### FEATURES:

- Quick Installation of Flat Panel Retrofit Kit in existing luminaire without the need to break the ceiling plenum.
- Edge-Lit LED light source has a very thin profile.
- Available in standard CCT's (3500K, 4000K, 5000K)
- Design prevents any gaps from the retrofit fit in the existing troffer

### CONSTRUCTION:

- EdgeLit panel featured aluminum frame and steel back for rigid support
- Standard Dimension for 1x4, 2x2 & 2x4 Retrofits
- Fits most existing Troffers

### CONTROL:

Compatible with standard 0-10v dimming controls

### FORM AND FIT:

MaxLite recommends that a product sample is tested before projects begin to check fit of the retrofit kit. The retrofit kit is designed to fit into most preexisting troffers (lensed and parabolic).


### WARRANTY:

10-year standard warranty with labor allowance\*

(further details available at [www.maxlite.com/warranties](http://www.maxlite.com/warranties))

\*Warranty Limitations: Product must be rated for the application per the Product Data Sheet (PDS); operated < 16 hrs; in ambient of -4° to 104°F

\*Up to \$25/unit; labor allowances of up to \$500/unit available for purchase – contact MaxLite representative for details.



FAMILY	SIZE/LENGTH	WATTAGE	CCT	BATTERY BACKUP	SENSOR
FPR= Flat Panel Retrofit Kit	14EP= 1'x4'	30= 30 watts	35= 3500K	(OMIT)= None	(OMIT)= None
	22EP= 2'x2'	30= 30 watts	40= 4000K	1EM= Emergency Battery	MS= Bi-Level Motion Sensor with Daylight Harvesting and remote control commissionable
	24EP= 2'x4'	40= 40 watts	50= 5000K		

### NOTES:

1. In the event of a power failure, the battery backup unit switches to emergency mode and operates the fixture for a minimum of 90 minutes.
2. EM and EMMS options are not DLC Listed

### SPECIFICATIONS:

		FPR14EP3040	FPR22EP3040	FPR24EP4040
ITEM	SPECIFICATION	DETAILS		
GENERAL PERFORMANCE	Color Temperature (K)	4000K		
	Lumens Delivered (lm)	2,999	3,080	4,136
	Efficacy (lm/W)	102	102	102
	Lumen Maintenance (L70)	100,000 hours		
	CRI (Min)	≥ 80		
ELECTRICAL	Power Consumption (W)	30	30	40
	Power Factor	> .0.9		
	Input Voltage	120V-277V		
PHYSICAL	Dimensions (inches)	45.8" x 10.3" x 0.4"	22.1" x 21.8" x 0.4"	45.8" x 22.1" x 0.4"
	Ambient Temperature	-4° to 104°F		
QUALIFICATION	Qualification	ETL Classified , FCC, DLC Standard		
	Material Usage	RoHS compliant; no mercury		
	Environment	Indoor		
	Warranty	10 year standard warranty*		

### ORDERING\*:

ORDER CODE	MODEL	COLOR TEMPERATURE (CCT)	SIZE	WATTS	INPUT VOLTAGE
102854	FPR14EP3035	3500K	1'x4'	30	120-277V
102855	FPR14EP3040	4000K			
102856	FPR14EP3050	5000K			
102863	FPR22EP3040	4000K	2'x2'		
102864	FPR22EP3050	5000K			
102870	FPR24EP4035	3500K	2'x4'	40	
102871	FPR24EP4040	4000K			
102872	FPR24EP4050	5000K			

Lighting layouts and spacing criteria available upon request

\*Please contact your MaxLite representative to order products that don't have order codes listed here.