

LAMP READY TROFFER

MLRT









PRODUCT DESCRIPTION:

The MaxLite "Lamp Ready" Troffer series provides architects, specifiers, and buyers with a UL listed fixture engineered to operate the latest single ended LED T8 lamps on the market. Offering classic prismatic diffuser and recessed housing, these fixtures come pre-wired for single ended operating LED lamps for contractor ready installation as new or remodel fixtures.

FEATURES:

- •Lamps not included
- •Lead wires are 7' for tandem wiring, eliminating back and end
- •Sockets are wired in series via non-shunted sockets
- •IC rated
- •Fits standard T-bar grid (drop ceilings)
- •Room side access door to service and upgrade LED T8 tubes

CONSTRUCTION:

- •Engineered and UL rated to take up to 10W per set of lamp holders (2x2) and 22W per set of lamp holders (2x4)
- •Indoor and damp rated use
- •Wiring is 18 AWG solid to allow 120-277V operation where lamp specification allows

WARRANTY:

•Indoor 5 year warranty on parts, materials and workmanship

	λk		
110	0	•	3.3"
1	23.7"		1
	23./		

ORDERING INFORMATION				
ORDER NUMBER	MODEL	WATTS (NOMINAL)	DESCRIPTION DIMENSION (L" x W" x	
97869	MLRT22XT8	40W	TROFFER LAMP READY 2X2 4 LAMP T8 LED 120-277V 23.7" x	
97870	MLRT24XT8	88W	TROFFER LAMP READY 2X4 4 LAMP T8 LED 120-277V 23.7" x 47.4	

NOTES:



^{1.} This product is specifically engineered and listed for use with MaxLite Single Ended conductor LED lamps. Maximum lamp wattages cannot exceed stated levels without voiding warranty. Use with any other branded lamps should be confirmed by a qualified electrician prior to use.

LAMP READY TROFFER MLRT SERIES

Page: 2 of 2

SPECIFICATIONS:		MLRT22XT8	MLRT24XT8	
ITEM	SPECIFICATION	DETAILS		
FLEGTBIOAL	Input Voltage	Max 10W Per Lamp	Max 22W Per Lamp	
ELECTRICAL	Power Consumption	Per Lamp Spec		
PHYSICAL	Dimension	24" x 24"	24" x 48"	
	Housing	Steel		
	Lens	Prismatic		
	Mounting	Fits standard grid for drop ceilings		
	Operating Temperature	Per lamp spec		
CERTIFICATION	Certification	UL for single ended LED lamps*		
	Material Usage	RoHS compliant; no mercury		
	Environment	Indoor/ Damp		
	Warranty	5 Year		

^{*} See reference diagram adjacent. Must be followed

IMPORTANT WARNING:

