

## RHLED Outdoor LED Remote Head

Project:	
Туре:	
Catalog #:	



#### Also available in Thermoplastic

### **ILLUMINATION**

- · Long lasting, efficient, ultra bright white LED lamp heads.
- High performance chrome-plated metallized reflector and glass lens with 8 or 12 LED's in each lamp head for optimal light distribution.
- Adjustable LED lamp heads increases center-to-center spacing.

### **ELECTRICAL**

 Powered from low voltage power source with low voltage wiring (not provided).

#### **MOUNTING**


- · Universal mounting base mounts to single-gang switch box.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.
- Suitable for wall or ceiling mount.

#### HOUSING

- Available in both engineering grade, high-impact resistant thermoplastic or premium grade die-cast aluminum housing.
- Sealed and gasketed in standard gray or optional black finish.

# • Five year warranty.

- UL Listed with approved Best Lighting Products.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.



#### **FIXTURE COMPATIBILITY CHART**

Reference individual unit equipment specification sheets for remote load capacity availability.

MODEL TYPE	3.6V	9.6V	MV
LEDCXTEU-RC		Х	Х
CLPU-RC		Х	Х
CKXTEU-RC	Х		X
LEDR-5HO	Х		Χ
LEDTFX-2		Х	Х
E-1-RC	X		Х
CEU-RC	X		Х

Sample Part Number: RHLED-WP-R2

#### **ORDERING INFORMATION**

MODEL	L No. of HEADS		OPTIONS		HOUSING		VOLTAGE		COLOR		LAMP TYPE <sup>1</sup>	
RHLED	1	Single Head	Blank	For standard non-self- diagnostic fixtures	PWP	Thermoplastic	3.6V	For use with 3.6V batteries	Blank	Gray	Blank	8 LEDs 1W
	2	Double Head	SDT	For use with fixtures with a self-diagnostic option	WP	Die-cast	9.6V	For use with 9.6V batteries	В	Black	HL	12 LEDs 1.5W
							MV	For use with 3.6V, 6V, 9.6V & 12V batteries				

Notes.

<sup>1.</sup> Wattage rating stated per head.