



ABS Plastic Frame Self Luminous Exit Sign

DATE:	COMMENTS:
PROJECT	

FEATURES

- Requires no electricity or external light source.
- Maintenance free with no lamps or batteries to replace.
- Easy to install with no wiring required.
- Ideal for damp, wet, hazardous, and extreme temperature applications.
- Special wording and pictographs are available.
- Service life options of 10 or 20 years are available.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION SLX-BW

1. SERIES	2. SERVICE LIFE	3. FACE COUNT	4. FACE COLOR	5. FRAME COLOR
SLX-BW	-	-	-	-
	10 10 Years 20 20 Years	1 Single 2 Double	BK Black G Green R Red	BK Black GY Gray WH White
6. MOUNTING	7. OPTIONS			
MTEBP Universal Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount	BLANK = NO OPTION CW Custom Wording VR 1/8" Vandal Resistant	t Lens (Includes Tamperproof Screv	vs)	

ACCESSORIES; ORDER SEPARATELY

- WG-20.0LX19.0WX9.0D = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D = Wireguard, Length: 26", Width: 19", Depth: 9"

SLX-BW

ABS Plastic Frame Self Luminous Exit Sign



SPECIFICATIONS

CONSTRUCTION

 Flame retardant, UV stabilized, injection molded ABS frame

LETTERS

• 6.0" high; 0.75" stroke

ARROWS

Universal chevrons

VIEWING DISTANCE

100 ft visibility rating

TECHNOLOGY

Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas-a natural hydrogen isotope.

WEIGHT

Single Face: 2.5 lbsDouble Face: 5 lbs

TEMPERATURE RATING

From -67°F to 176°F

APPROVALS

- UL Listed to standard UL 924 & CAN/ ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class I, II, and III conditions

WARRANTY

 Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

