

SLX-RB

ABS Plastic Frame Self Luminous Exit Sign

DATE:	COMMENTS:
<input type="text"/>	<input type="text"/>
PROJECT	<input type="text"/>
<input type="text"/>	<input type="text"/>

FEATURES

- Requires no electricity or external light source.
- Maintenance free with no lamps or batteries to replace.
- Easy to install with no wiring required.
- Ideal for damp, wet, hazardous, and extreme temperature applications.
- Special wording and pictographs are available.
- Service life options of 10 or 20 years are available.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS
Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION SLX-RB

1. SERIES	2. SERVICE LIFE	3. FACE COUNT	4. FACE COLOR	5. FRAME COLOR
SLX-RB	-	-	-	-
	10 10 Years 20 20 Years	1 Single 2 Double	BK Black G Green R Red	BK Black GY Gray WH White
6. MOUNTING	7. OPTIONS			
MTEBP Universal Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount	BLANK = NO OPTION CW Custom Wording VR 1/8" Vandal Resistant Lens (Includes Tamperproof Screws)			

ACCESSORIES; ORDER SEPARATELY

- WG-20.0LX19.0WX9.0D = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D = Wireguard, Length: 26", Width: 19", Depth: 9"

SLX-RB

ABS Plastic Frame Self Luminous Exit Sign



SPECIFICATIONS

CONSTRUCTION

- Flame retardant, UV stabilized, injection molded ABS frame

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- Universal chevrons

VIEWING DISTANCE

- 100 ft visibility rating

TECHNOLOGY

- Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas—a natural hydrogen isotope.

WEIGHT

- Single Face: 2.5 lbs
- Double Face: 5 lbs

TEMPERATURE RATING

- From -67°F to 176°F

APPROVALS

- UL Listed to standard UL 924 & CAN/ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class I, II, and III conditions

WARRANTY

- Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

