



LED WALLMAX SMALL WALL PACK

WPS Series



WPS30A model

DIMENSIONS:



PRODUCT DESCRIPTION:

MaxLite's standard WallMax™ LED Wall Packs with new reflectors increase light output and efficacy to reduce shadows and create safe, brightly-lit outdoor environments in parking garages and entrances, public areas, schools, hospitals, hotels and outdoor walkways nationwide. The 30-watt LED fixture is an energy-efficient replacement for 100- and 150-watt metal halide fixtures, respectively. The fixtures are rebatable, save energy, lower maintenance costs, and prevent light pollution.

FEATURES:

- Replaces up to 150 Watt Metal Halide
- 145,000-hour L70 lifetime, TM-21 standards @ 25°C
- Heavy-duty cast aluminum housing is polyester powder coated to be rust and corrosion proof
- High-quality shatter-resistant glass
- Sealed fixture is dirt and bug free
- Top, bottom, and side knockouts for mounting convenience
- Available with Dusk to Dawn sensor
- 0-10V dimming driver standard; compatible with IEC 60929 rated fluorescent or LED 0-10V dimmers
- LM-79/80 data available
- 5 Year Limited Warranty

CONTROLS:

120-277VAC Photocontrol: Voltage-specific photocontrols power the fixture when light levels reach 20 lux or below, and turn it off at 30 lux or higher. The operating temperature of the photocontrols are -30°F-120°F. Photocell mounted external.

PHOTOMETRICS:

All .IES files available online. Please see page 3 for Iso-footcandle layouts.

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: WPS30AU50BPC12

WPS		A	U	50		
FAMILY	NOMINAL POWER, EQUIVALENCY	GENERATION	VOLTAGE	CCT	FINISH	OPTION
WPS= Small Wall Pack	30= 30W, 150W MH equivalent	A= Generation A	U= 120-277V, std 3= 347V	50= 5000K	B= Bronze, std W= White	(OMIT)= None PC12= 120V Integral Photocontrol

SPECIFICATIONS:

WPS30AU50BXXX

ITEM	SPECIFICATION	DETAILS
GENERAL PERFORMANCE	Input Power (W)	26
	Lumens Delivered (lm)	2195
	Efficacy (lm/W)	85
	CRI	≥80
	Lumen Maintenance (L70, TM-21 @ 25°C)	≥145,000
	Color Temperature	5000K
	Spacing Criteria	Available Upon Request
	Color Consistency	Proprietary binning for uniform color
ELECTRICAL	Power Factor (120V/277V)	0.99/0.94
	Input Voltage	120-277V standard; 347V available
PHYSICAL	Weight (lb.)	9.03
	Housing	Aluminum
	Lens	High quality shatterproof glass
	Mounting	Fits electrical box or mount directly
CERTIFICATION	Certification	LM-79, LM-80, TM-21, cULus
	Environment	Outdoor, Wet locations
	Warranty	5 years

Lighting layouts and spacing criteria available upon request

ORDERING*:

ORDER CODE	MODEL NUMBER	OPTIONS	VOLTAGE	FINISH	NOMINAL WATTAGE	CCT
95182	WPS30AU50BPC12	120-277V Button Photocontrol	120-277V	Bronze	30	5000K
95185	WPS30AU50B	None	120-277V			
95189	WPS30AU50W	None	120-277V	White		
95193	WPS30A350B	None	347V	Bronze		

*Please contact your MaxLite representative to order products that don't have order codes listed here.

CONSTRUCTION:

Fixture: This rust and corrosion proof fixture is constructed of a heavy-duty cast aluminum one-piece housing, with a polyester powder coat. The fixture is sealed to be dirt and bug proof.

Lens: High quality shatter-resistant glass

LED Module: Aluminum components in the LED module act as heat sinks to reduce heat and add to life. The module uses directional settings to control the fall of light and the light levels. This makes the fixture an efficient replacement for metal halide and high pressure sodium fixtures, while reducing wattage and extending life.

Reflector: Internal polished aluminum reflector maximizes light output.


LED Driver: Self contained driver meets UL 1310 UL 48 Class2

Finish: Dark Bronze or white finish available; polyester powdercoated.

Installation: Can mount to recessed outlet boxes or directly to surfaces

PHOTOMETRICS:

WPS30AU50B



WPS30AU50B
2197 Lumens
15' Mounting Height

Foot-candle Correction Factor:

New Height:	10'	12'	15'	18'	20'
Multiply by:	2.3	1.6	1.0	.69	.36