

ILLUMINEX Series

THERMOPLASTIC LED EXIT

Model Number:	Approvals:
Accessories:	
Job:	Type:

FEATURES

- Ultra-compact, low-profile design
- Easy to install, snap together design
- Rugged, injection-molded UL94 V-0 flame retardant, high-temperature thermoplastic housing
- Universal style - includes 2 face plates, a back plate and mounting canopy
- Brown-out, short circuit and voltage surge protection
- Overcharge protection
- Maintenance-free NiCad battery
- Universal J-Box mounting system - Ceiling, wall or end mount
- ETL listed 90 minute emergency run time, 24 hour recharge time
- Constant, uniform illumination by long-life, high intensity, red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke
- Chevron-style, universal arrow knockouts
- 120/277V dual primary, 60Hz input
- Standard finishes: Black or white
- Suitable for damp location



The Illuminex Series LED Exit Sign combines an attractive, easy-to-install compact contemporary design with proven, ultra-reliable electronics to provide the very best in energy efficient emergency lighting. ILX units are completely self-contained and features universal mounting, canopy included.

WARRANTY

Any component that fails due to manufacturers defect is guaranteed for 1 year with a separate 5 year pro-rated warranty on the battery. The warranty does not cover physical damage, abuse or acts of God. Manufacturer reserves the right to charge for such repairs if deemed necessary.



SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

ORDERING INFORMATION Example: ILX-R-EM-WH

Series	LED Color	Power Source	Finish	Accessories ² (Field Installed)
ILX ¹	R = Red	AC = AC Only	WH = White	ER1-KIT = 1' Pendant Mount Kit
	G = Green	EM = NiCad Battery	BL = Black	ER2-KIT = 2' Pendant Mount Kit
				VEPA = Pendant Adapter
				WG-1 = Wire Guard (Back Mount)
				WG-2 = Wire Guard (End Mount)
				WG-3 = Wire Guard (Ceiling Mount)
				XG-1 = Poly Guard (Back Mount)
				XG-3 = Poly Guard (Ceiling Mount)

¹ Includes 2nd exit face and backplate
² Order as separate line item

