

Bi-split : SUV2-H18/3CFA-N SMVH09B-2A2A3NG SMVH09B-2A2A3NG
 Bi-split : SUV2-H18/3CFA-N SMVH09B-2A2A3NG SMVH12B-3A2A3NG
 Tri-split : SUV3-H24/3CGA-N SMVH09B-2A2A3NG SMVH09B-2A2A3NG SMVH12B-3A2A3NG



Features		SMVH09B-2A2A3NG (9000 Btu)	SMVH12B-3A2A3NG (12000 Btu)	
Indoor units	Area	m ²	15-25	25-35
	Airflow (H/M/B/SB*)	m ³ /h	520/440/230/150	580/500/300/230
	Dehumidification	L/h	0,80	1,40
	Min/max temperature range	°C	16/31	16/31
	Dimensions (W x H x D)	mm	790 x 275 x 195	821 x 283 x 200
	Net weight	Kg	9	10
	Sound pressure (H/M/B/SB*)	dB	38/34/21/19	40/35/22/20
	Acoustic power (H/M/B/SB*)	dB	51/47/34/32	53/48/35/33
Hot	Heating capacity	W	2800	3650
	Minimum heating capacity	W	400	600
	Max heating capacity	W	4100	5130
	Nominal power consumed	W	745	970
	SCOP	-	4	4
	Energy class	-	A+	A+
	Outdoor unit operating temperature range	°C	-15-24	-15-24
Cold	Cooling capacity	W	2600	3500
	Minimum cooling capacity	W	400	500
	Max cooling capacity	W	3300	4000
	Nominal power consumed	W	750	1010
	SEER	-	6,1	6,1
	Energy class	-	A++	A++
	Outdoor unit operating temperature range	°C	18-48	18-48

* High / Mid / Low / Super bass



Ecological gas



Reversible



Works down to -15°C



Wi-Fi Option



Silent



Ionizer cold plasma



Night Mode

MULTISPLIT



Features			SUV2-H18/3CFA-N	SUV3-H24/3CGA-N
Outdoor units	Nominal voltage	V	220-240	220-240
	Rated frequency	Hz	50	50
	Electrical protection	A	20	25
	Min/max voltage	V~	194/264	194/264
	SEER	-	6.10	6.10
	SCOP	-	4	4
	Energy class		A++/A+	A++/A+
	Sound pressure	dB	54	55
	Acoustic power	dB	62	68
	Dimensions (W x H x D)	mm	960 x 700 x 396	990 x 790 x 426
	Net weight	Kg	45	55
	Compressor		Panasonic	Panasonic
	Gas type		R32	R32
	Gas quantity	Kg	1,10	1,10
Connection diameters	po (mm)	1/4 (6,35) 3/8 (9,52)	1/4 (6,35) 3/8 (9,52)	
Hot	Heating capacity	KW	5,20	7
	Nominal absorbed power	KW	2,25	3,2
	Nominal power consumed	KW	1,25	1,7
Cold	Cooling capacity	KW	5,20	7
	Nominal absorbed power	KW	2,5	3,3
	Nominal power consumed	KW	1,40	1,90



Auto Mode



Dehumidification
Mode



ReadyClim



LED Display



Timer



Energy class

SCOP
4.0

SEER
6.1