HOW TO ASSEMBLE



SJX-1WH / SJX-1GY

BEFORE YOU BEGIN:

- Make sure the machine is not plugged in prior to assembling the machine.
- Make sure the POWER SWITCH is in the OFF position **O** prior to assembling the machine.
- Before using the juicer for the first time, clean all parts, except for the MAIN BODY, in soapy water. Then rinse and dry thoroughly.

WARNING: Never immerse the MAIN BODY in water.



STEP 1:

Make sure that the PRESSURE PLUG is fully inserted into the pulp outlet on the bottom of the AUGER HOUSING (see page 13 for details). Place the AUGER HOUSING on top of the MAIN BODY, making sure both the juice and pulp outlets are fully seated.



STEP 2:

Push the AUGER firmly into the center of the AUGER HOUSING, making sure the AUGER is fully seated on the bottom.



STEP 3:

Place the JUICING ASSEMBLY over the AUGER and into the AUGER HOUSING. Align the arrow ▲ on the JUICING ASSEMBLY to the unlocked position on the MAIN BODY and twist it clockwise until it clicks into the locked position .

The arrow \triangle should align with the lock symbol $\widehat{\square}$ to complete the assembly.



STEP 4:

Place the JUICE CONTAINER and the PULP CONTAINER under the relevant outlets. Make sure the JUICE CAP is open before you begin juicing.

Your Shine Juicer is now fully assembled.