

INSTRUCTIONS

Installation of Rear Seat Cargo Rack for RZR 4- Seater 2014+



TOOLS NEEDED:

- Phillips Screwdriver
- 7/16" Socket or Crescent Wrench
- 5/8" Socket or Crescent Wrench

*NOTE: Rack comes in 3 pieces (2) Sides and (1) Middle Piece and is easily put together using the tools above. No drilling required.



1. Remove Rear Seats from Machine
2. Start by taking (1) Side piece and Middle piece. Using nuts and bolts Supplied, loosely assemble.
3. Repeat by attaching Opposite side to Middle piece.
4. Once all nuts and bolts are attached, start tightening until all are tightened.
5. Next take assembled rack and place Into clips that seats were attached to.
6. There are 4 Bolts and 5/8" Nuts on both sides that attach to the bases. They are loose

when delivered so you can push rack into place. Push rack as far to the back as you can and tighten up 8 bolts with 5/8" crescent wrench.

7. Load up & GOOOO!

Thank you for your Business and Have A DiRtY DAY!

Questions call: 435-467-7401

NOTE: All of our Cargo Racks have previously been put together and installed in a RZR to assure fitment. You may notice slight mars around screw holes because of this. Products are made from aluminum so they will not rust. These products are made by human hands here in the USA.