

#### Features:

- Stainless steel casing
- Superior Mitsubishi Compressor
- 5 Metres of programmer cable
- Cascade any number of units
- Volt Free Switching control
- Heating & cooling functions
- Intelligent defrosting
- Built-in powerfull wilo pump
- Precision electronic expansion valve
- High efficiency heat exchanger
- Refrigerant diagnostic gauges
- Working range +43°C to -15°C
- Low current soft start
- 5 Year Warranty\*

\*see warranty terms and conditions



Hinged door panel for easy installation & access



Intelligent touch screen controller

#### Specifications:

Model	CE-H12
ERP Rating	A++
Rated Capacity @35°C Water/ 20°C Ambient	11.8kw
Rated Capacity @35°C Water/ 7°C Ambient	9.4kw
Rated Capacity @45°C Water/ 20°C Ambient	10.7kw
Rated Capacity @45°C Water/ 7°C Ambient	8.5kw
Rated Capacity @7°C Water/ 25°C Ambient	7.9kw
Rated Power Input	3.5kw/16.8A
Max Power Input	4.8kw/22.5A
Compressor Make/Model	MITSUBISHI/LN38VBRMC
Noise	≤52dB(A)
Power Supply	220-240V AC-50Hz
Outlet Water Temperature	35°C-60°C
Protection Class	IPX4
Anti-electric Shock Class	Class I
Refrigerant/Charge	R410A- 1500g
Minimum Water Flow Required	2.5m <sup>3</sup> /h
Water Pump Model	Wilo 25/8
Water Connections	1" Male
Climate Type	-15~43°C
Product Dimension L x W x H	755/370/1090mm
Net Weight	81Kg