

Features:

- Stainless steel casing
- Copeland Scroll Compressor
- 5 Metres of programmer cable
- Cascade any number of units
- Volt Free Switching control
- Heating & cooling functions
- Intelligent defrosting
- Built-in powerfull wilo pump
- Precision electronic expansion valve
- High efficiency heat exchanger
- Refrigerant diagnostic gauges
- Working range +43°C to -15°C
- Low current soft start
- 5 Year Warranty*

*see warranty terms and conditions



Specifications:

Model	CE-H17
ERP Rating	A++
Rated Capacity @35°C Water/ 20°C Ambient	19.0kw
Rated Capacity @35°C Water/ 7°C Ambient	14.3kw
Rated Capacity @45°C Water/ 20°C Ambient	17.6kw
Rated Capacity @45°C Water/ 7°C Ambient	13.5kw
Rated Capacity @7°C Water/ 25°C Ambient	10.2kw
Rated Power Input	3.7kw/17.8A
Max Power Input	4.98kw/23.1A
Compressor Make/Model	COPELAND/ZW51KWP-PFZ-522
Noise	≤60dB(A)
Power Supply	220-240V AC-50Hz
Outlet Water Temperature	35°C-60°C
Protection Class	IPX4
Anti-electric Shock Class	Class I
Refrigerant/Charge	R410A-2800g
Minimum Water Flow Required	3.0m ³ /h
Water Pump Model	Wilo PUN-200EH
Water Connections	1" Male
Climate Type	-15~43°C
Product Dimension L x W x H	765/717/895mm
Net Weight	110kg



Hinged door panel for easy installation & access



Intelligent touch screen controller