

Features:

- Stainless steel casing
- Superior Mitsubishi Compressor
- 5 Metres of programmer cable
- Cascade any number of units
- Volt Free switching control
- Heating & cooling functions
- Intelligent defrosting
- Built-in powerfull wilo pump
- Precision electronic expansion valve
- High efficiency heat exchanger
- Refrigerant diagnostic gauges
- Working range +43°C to -15°C
- 5 Year Warranty*

*see warranty terms and conditions



Specifications:

Model	CE-H6
ERP Rating	A++
Rated Capacity @35°C Water/ 20°C Ambient	6.83kw
Rated Capacity @35°C Water/ 7°C Ambient	5.85kw
Rated Capacity @45°C Water/ 20°C Ambient	6.20kw
Rated Capacity @45°C Water/ 7°C Ambient	5.32kw
Rated Capacity @7°C Water/ 25°C Ambient	4.35kw
Rated Power Input	1.50kw/6.88A
Max Power Input	2.25kw/10.3A
Compressor Make/Model	MITSUBISHI/RN222VHFMC
Noise	≤52dB(A)
Power Supply	220-240v AC-50Hz
Outlet Water Temperature	35°C-60°C
Protection Class	IPX4
Anti-electric Shock Class	Class I
Refrigerant/Charge	R410A-800g
Minimum Water Flow Required	1.2m ³ /h
Water Pump Model	Wilo 15/6
Water Connections	1"
Climate Type	-15~43°C
Product Dimension L x W x H	655/355/986mm
Net Weight	58kg



Hinged door panel for easy installation & access



Intelligent touch screen controller