

Features:

- Stainless steel casing
 - Superior Mitsubishi Compressor
 - 5 Metres of programmer cable
 - Cascade any number of units
 - Volt Free Switching control
 - Heating & cooling functions
 - Intelligent defrosting
 - Built-in powerfull wilo pump
 - Precision electronic expansion valve
 - High efficiency heat exchanger
 - Refrigerant diagnostic gauges
 - Working range +43°C to -15°C
 - Low current soft start
 - 5 Year Warranty*
- *see warranty terms and conditions



Specifications:

Model	CE-H8
ERP Rating	A++
Rated Capacity @35°C Water/ 20°C Ambient	9.0kw
Rated Capacity @35°C Water/ 7°C Ambient	7.6kw
Rated Capacity @45°C Water/ 20°C Ambient	8.7kw
Rated Capacity @45°C Water/ 7°C Ambient	7.0kw
Rated Capacity @7°C Water/ 25°C Ambient	5.4kw
Rated Power Input	1.9kw/8.4A
Max Power Input	2.5kw/11.3A
Compressor Make/Model	MITSUBISHI/LN28VBRMC
Noise	≤52dB(A)
Power Supply	220-240v AC-50Hz
Outlet Water Temperature	35°C-60°C
Protection Class	IPX4
Anti-electric Shock Class	Class I
Refrigerant/Charge	R410A-1500g
Minimum Water Flow Required	1.3m ³ /h
Water Pump Model	Wilo 28/8
Water Connections	1"
Climate Type	-15~43°C
Product Dimension L x W x H	755/370/1090mm
Net Weight	81kg



Hinged door panel for easy installation & access



Intelligent touch screen controller