

Features:

- Stainless steel casing
- Superior Mitsubishi Compressor
- 5 Metres of programmer cable
- Cascade any number of units
- Volt Free Switching control
- Heating & cooling functions
- Intelligent defrosting
- Built-in powerfull wilo pump
- Precision electronic expansion valve
- High efficiency heat exchanger
- Refrigerant diagnostic gauges
- Working range +43 to -15
- 5 Year Warranty*

*see warranty terms and conditions



Specifications:

Model	CE-iH6-18
ERP Rating	A++
Rated Capacity @35°C Water/ 20°C Ambient	17.0kw
Rated Capacity @35°C Water/ 7°C Ambient	13.6kw
Rated Capacity @45°C Water/ 20°C Ambient	14.9kw
Rated Capacity @45°C Water/ 7°C Ambient	13.0kw
Rated Capacity @7°C Water/ 25°C Ambient	9.9kw
Rated Power Input	3.9kw/18.5A
Max Power Input	4.7kw/21.3A
Compressor Make/Model	MITSUBISHI/MNB42FDAMC
Noise	≤60dB(A)
Power Supply	220-240v AC-50Hz
Outlet Water Temperature	35°C-60°C
Protection Class	IPX4
Anti-electric Shock Class	Class I
Refrigerant/Charge	R410A-3600g
Minimum Water Flow Required	3m ³ /h
Water Pump Model	Wilo PUN-200EH
Water Connections	1" Male
Climate Type	-15~43°C
Product Dimension L x W x H	765/717/895mm
Net Weight	113kg



Hinged door panel for easy installation & access



Intelligent touch screen controller