

Water Fan Coils REVERSO

Heating & Cooling

Reverso High Wall

Features:

- Reverso HW, is the hydronic fan coil for high wall Installation.
- The features that distinguish it from products of the same category are:
- Super thin thickness only 12 cm
- Minimum noise level below the audible threshold 20 dB (A)
- DC Inverter technology
- Low power consumption only 4 Watts
- Modern design
- Front panel in tempered glass crystal
- Practically eternal pleated stainless steel filters
- Tangential aluminum fan for greater efficiency
- Controls with remote control and on the wall
- Wi-Fi controls for easy mobile phone manage-ment (Optional)
- Double flap for accurate control of the air direction
- Eight speed programsModular thermal power
- Cooling function Heating function
- Dehumidification function Purification function
- Modular heating capacities from 0.5 to 4 Kw

- 5 Year Warranty

*see warranty terms and conditions







Reverso Floor / Wall / Ceiling

Features:

- Reverso FS, is the hydronic fan coil for low and horizontal ceiling installation.
- The features that distinguish it from products of the same category are:
- Super thin thickness only 12 cm
- Minimum noise level below the audible threshold 20 dB (A)
- DC Inverter technologyLow power consumption only 4 Watts
- Modern design
- Front panel in tempered glass crystal
- Radiant panel on request
- Practically eternal pleated stainless steel filters
- Tangential aluminum fan for greater efficiency
- Controls on the machine or on the wall
- Wi-Fi controls for easy mobile phone manage-ment via convenient App (Optional)
- Adjustable air outlet grilles in extruded aluminium
- Eight speed programs
- Modular thermal power for each single size
- Cooling function Heating function
- Dehumidification function Purification function
- Sizes of thermal powers from 0.5 to 4, 7Kw

- 5 Year Warranty

*see warranty terms and conditions





















Water Fan Coils REVERSO

Heating & Cooling

Reverso Bathroom & Kitchen

Features:

- Reverso BT, is the hydronic fan coils for the bathroom and beyond
- The features that distinguish it from products of the same category are:
- Super thin thickness only 12 cm
- Minimum noise level below the audible threshold 20 dB (A)
- DC Inverter technology
- Low power consumption only 4 Watts Modern design
- Front panel in tempered glass crystal
- Standard 200 watt radiant front panel
- Practically eternal pleated stainless steel filters
- Tangential aluminum fan for greater efficiency
- Controls with remote control and convenient LCD display
- It can be installed behind normal doors
- Wi-Fi controls for easy mobile phone manage-ment (Optional)
- Adjustable air outlet grilles in extruded aluminium
- Eight speed programs
- Modular thermal power through the various fan speed configurations
- Cooling function Heating function
- Dehumidification function Purification function
- Heating capacities 1.65 Kw
- 5 Year Warranty
- *see warranty terms and conditions







Specifications

Model	U.M.
Cooling Capacity	KW
Heating Capacity	KW
Air flow (min-max)	m3/h
Input power (min-max)	watt
Sound pressuore level (SPL)	db(A)
Width	mm
Height	mm
Deep	mm
Invert DC motor low consumption	
Aluminum cross fan	
Remote hand set	
LCD display	
Pleated stainless steel filter	
Front panel in tempered glass crystal	
Machine structure in powder-coated steel	
Voltage	V-hz
Optional	
Touch screen Lux command	
Black Touch screen Top command Wi-Fi	
Water probe	
2 way valve + pipes kit	
Feet	
Frontal radiant panel	
Condensete collector tray	

High Wall

HW400	HW600	HW800
1.30	1,82	2,58
1,83	2,7	3,78
55-315	240-450	310-540
4-11	5-14	8-17
20	22	23
873	1065	1257
383	383	383
120	120	120
Si	Sí	Si
Si	Si	Si
20-50	220-50	220-50
ptional	Optional	Optional
No	No	No

Floor / Wall / Ceiling

Bathroom

FS800	BT400	
3,73	1,45	
4,69	1,65	
310-540	120-225	
8-17	4-11	
23	20	
1257	565	
553	1100	
120	120	
Si	Si	
Si	Si	
No	Si	
No	Si	
Si	Si	
Si	Si	
Si	Si	
220-50	220-50	
Optional	Optional	
Optional	No	
Optional		
Optional	No	



Back aesthetic panel













