



AH-64
Apache Helicopter
R&D Team



OIL STABILIZER

- Extends oil life up to 100%.
- Improves horsepower.
- Protects against friction and engine wear.
- Protects against viscosity breakdown.
- Improves oil pressure and reduces temperature.
- Reduces dry starts.
- Reduces knocking.
- Compatible with synthetics.
- Up to 40% reduction in scarring in the 4-Ball Wear Test.
- Up to 68% reduction in wear metals.
- Up to 60% faster in reducing oil temperatures.
- Anti-foaming qualities to increase performance.

Works great and field-tested on Race Cars, Conventional Cars, SUV's & Trucks, Marine Engines, RV, Industrial Motors, Class 1-8 Trucks and Buses.

NANO ^{Pro MT}™

Conor Daly
Nano Racing Team
Indycar Series

18

ncrcenter.com





MADE IN

THE USA

NANO ProMT Oil Stabilizer is a Military Tough/Race Ready, extreme pressure Oil Stabilizer engineered to protect vital engine components against friction and engine wear. Using NANO ProMT Oil Stabilizer reduces oil temperatures up to 60% faster than standard lubricants, it reduces dry starts and viscosity breakdown for improved horsepower and oil pressure. All of which extends oil life up to 100%.

DESCRIPTION	SYNTHETIC OIL STABILIZER
PART#	NDT32OS
UPC CODE	853770004149
SCC CODE	10853770004146
HARMONIC CODE	3811.21.00
PACKAGE CONTENTS	32 oz
SELLING UNIT WEIGHT	2.0833 pounds
SELLING UNIT DIMENSION	3.43" x 3.43" x 11.75"
SELLING UNIT CUBE	.077 cubic feet
CASE PACK	12
CASE WEIGHT	25 pounds
CASE DIMENSION	14" x 10.75" x 12.5"
CASE CUBE	1.09 cubic feet
CASES PER PALLET	11
CASES/LAYER	4
LAYERS/PALLET	44
WEIGHT/PALLET	1,150 + 40 (total weight 1,190 lbs.)



NANO ProMT • 7427 Matthews Mint Hill Rd • Ste 201
 Mint Hill • NC 28227 • www.nanoprompt.com • Made in USA



SAFETY DATA SHEET

1. Identification

Product identifier Nano Oil Stabilizer

Other means of identification

SDS number NDT32OS

Part No. NDT32OS

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Nano ProMT LLC
Address 7427 Matthews Mint Hill Road, Suite 201
Mint Hill, NC 28227
Telephone Not available.
E-mail Not available.
Contact person Chris Hunter
Emergency phone number Not available.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1B
Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause drowsiness or dizziness. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Heavy Paraffinic		64742-54-7	40 - < 50

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Solvent-refined Heavy Paraffinic		64741-88-4	40 - < 50
Other components below reportable levels			3 - < 5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Avoid breathing mist or vapor. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)	PEL	5 mg/m3	Mist.
		2000 mg/m3 500 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

wear safety glasses with side shields (or goggles)

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Hazy

Physical state

Liquid.

Form

Liquid.

Color

Not available.

Odor

Petroleum

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

680 °F (360 °C) estimated

Flash point

275.0 °F (135.0 °C) estimated

Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	7.30 lbs/gal estimated
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.88

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting.

Information on toxicological effects

Acute toxicity	Narcotic effects.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.

Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	May cause cancer.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Distillates (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7) Known To Be Human Carcinogen.

Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4) Known To Be Human Carcinogen.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. One or more components are not listed on TSCA.
-------------------------------	--

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - No
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No**SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7)
 Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)

US. Massachusetts RTK - Substance List

Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-13-2016
Revision date	04-15-2016
Version #	02
HMIS® ratings	Health: 2* Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 0 Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.