



ACS Mould Eradication Additive

ACS Mould Eradication Additive will convert an ordinary decorative paint into a mould resistant coating for walls and ceilings. Please read and understand all the instructions and safety precautions carefully before you start.

ACS Mould Eradication Additive can be used with

EMULSIONS. GLOSS (OIL BASED) TILE GROUT.

EGGSHELL PAINTS. WALLPAPER PASTE. ACRYLIC (WATERBASED)

Preparation of surfaces

Prepare the surfaces to be painted by removing any loose or flaking material (including wallpaper) and filling all cracks and defects in the normal way.

Use **ACS Mould Wash Concentrate** to clean down the prepared area. Dilute 1 part concentrate to 19 parts water e.g. making 250ml concentrate as supplied up to 5 litres with water.

With a soft cloth, sponge or soft brush, wash down all areas to be painted with the diluted concentrate taking care to remove any oil, grease or surface debris.

Allow drying thoroughly.

Store any unused concentrate in its original container tightly closed and out of reach of children. Diluted material should be decanted into a suitable plastic (NOT METAL) container and stored for future use. Mark the container with an Indelible pen. Never use a food or drinks container and never leave a container unmarked.

Instructions as a paint additive

Carefully open the Mould Eradication Additive container and add the entire contents to the paint (1x 50ml of Mould Eradication Additive is enough to convert 2.5 litres of standard paint into a mould resisting paint;

2 x 50ml of Mould Eradication Additive is enough to convert 5 litres of paint). For wallpaper paste and tile grout add 50ml Mould Eradication Additive to 2.5 litres of product, mix thoroughly and apply in accordance with manufacturer's instructions.

STIR VERY THOROUGHLY BEFORE USE, especially at the bottom of the can, to disperse the additive throughout the paint. Apply the paint in the normal way according to the manufacturer's instructions.

Do not overcoat the antimould finish (or wallpaper over it) as this will effectively seal in the mould resistant finish and allow the mould to grow back.

N.B. - If an unfinished, textured wallpaper (blown vinyl, woodchip etc.) or similar is to be used then it should be hung after the diluted Mould Wash Concentrate has fully dried. The wallpaper should then be coated with the anti-mould finish as above.

Special Note

Areas that are subject to very severe or persistent mould growth may require treatment with one of the ready to use professional ACS antimould coatings. Contact Technical Sales at the address below for further details.

Safety Precautions

Read the container labels carefully before you start. Avoid contact with skin. Wear suitable protective clothing, gloves and eye and face protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical Advice. In case of accident or if you feel unwell seek medical advice immediately. Keep pets and unprotected people away from treated areas until thoroughly dry.

THIS PRODUCT IS APPROVED FOR USE UNDER THE CONTROL OF PESTICIDES REGULATIONS
FOR USE AS DIRECTED HSE No 8627

Advanced Chemical Specialties Ltd

9 Bofors Park Artillery Road Yeovil

Somerset BA22 8YH

Tel: 01935 414012

info@acslimited.co.uk

www.acslimited.co.uk