



THERMA-HYGROMETER

Operating Instructions

Product code:

810-145

INSTRUMENT OPERATION - Open the battery compartment and insert battery supplied. For the most accurate recording of ambient temperatures, the Therma-Hygrometer unit should be positioned away from direct sunlight and draughts.

MAX/MIN - Press the MAX/MIN button to display the maximum reading ('MAX' symbol displayed). Press the MAX/MIN button again to display the minimum reading ('MIN' symbol displayed). Press MAX/MIN button again to return to normal readings. To clear the MAX and MIN readings press the 'CLEAR' button when viewing the MAX or MIN readings.

Please note: Max/Min readings are not saved so if the battery is removed or drained the Max/ Min readings will be cleared.

°C/°F - Press the °C/°F button on the back of the instrument to switch between Centigrade and Fahrenheit


COMFORT INDICATORS - This unit displays comfort icons in the %rh display to show if the surrounding atmosphere is too dry, just right or too damp.

BATTERY REPLACEMENT - Replace the battery when the display dims, using an AAA or 1.5 volt equivalent. The battery is located under the battery cover at the rear of the instrument.

EMC/RFI - Instrument performance may be affected if operated within a high frequency

radio field, such as near a mobile phone, or if subjected to an electrostatic shock.

COMFORT



27 °C Temperature 20°C (°C)

GUARANTEE - This instrument carries a one-year quarantee against defects in either components or workmanship. During this period, products that prove to be defective will, at the discretion of ETI, be either repaired or replaced without charge. The product guarantee does not cover damage caused by fair wear and tear, abnormal storage conditions, incorrect use, accidental misuse, abuse, neglect, misapplication or modification. Full details of liability are available within ETI's Terms & Conditions of Sale at etiltd.com/terms. In line with our policy of continuous development, we reserve the right to amend our product specification without prior notice.









Specification

Range - temperature 0 to 50 °C Range - humidity 10 to 99 %rh

Resolution - temperature 0.1 °C/°F

Resolution - humidity 1 %rh

Accuracy - temperature ±1 °C

Accuracy - humidity ±5 %rh (30 %rh - 70 %rh at 25 °C)

Battery 1.5 volt AAA
Battery life 10000 hours

Display Dual custom LCD Dimensions 20 x 100 x 110 mm

Weight 135 grams













