

Technical Data Sheet

Platinum Mould Eradication Kit



Description:

The Platinum Mould Eradication Kit is designed to kill mould growth on walls, ceilings, window reveals, frames, doors, skirting boards etc.

Stage 1 - Spray

Spray MCS1 Mould Clear Solution onto the affected surface from a distance of 3-5cm. Treat visible mould **PLUS** 1 metre beyond. Repeat the treatment on badly affected areas after 10-15 minutes.

Areas to be treated

- **Painted and timber areas** - spray the area thoroughly with the MCS1 Mould Clear Solution.
- **Papered areas** - spray the paper. The MCS1 Mould Clear Solution acts as a biocide and stripping agent. Bag the mould contaminated paper and remove from the property. Treat the exposed plaster with a thorough spraying of MCS1 Mould Clear Solution.
- **General preparation** - Once the surface is dry, scrape off any loose flaking paint and rub down. Previously painted surfaces must be etched using sandpaper.
- **Coverage** - The solution should cover approximately 12.5m².

Stage 2 - Wipe

Rub the surface using the sponge provided. Allow approximately 30 minutes for the product to work, then rinse with warm soapy water. Repeat the treatment if necessary.

Stage 3 - Paint Additive

MCS3 Paint Additive is specially formulated to protect decorative finishes from future mould attack. This should be mixed into emulsion paint, primer, undercoat, varnish, gloss, wallpaper paste, textured paint or tile adhesive.

Add 100ml of MCS3 Paint Additive to 5L of water based paint (emulsion, vinyl, silk or matt).

Add 50ml of MCS3 Paint Additive to 5L of solvent based paint (primer, undercoat or gloss).

Blend the Paint Additive for at least 1 minute or until fully dispersed. Apply the paint in accordance with the manufacturers instructions.

Important - Condensation is usually increasingly the main cause of mould. To reduce this underlying problem, ensure adequate ventilation throughout the property. In very extreme cases of mould other remedial measures may be required.

Health & Safety:

Use biocides safely. Always read the label and product information before use.

MCS1 Mould Clear Solution (Ready to Use) - HSE No. 9453. Contains: Benzalkonium Chloride 0.95% w/w, 2-phenylphenol 0.24% w/w.

MCS3 Paint Additive - HSE No. 7656. Contains: 3-Iodo-2-Propynyl-n-Butyl Carbamate 14.85% w/w (148.6 g/l).

MCS1 Mould Clear Solution and MCS3 Paint Additive are approved for both Amateur and Professional Users.

Date: February 2017