

System 600  
**NEWTON 603 TILE**  
 Decoupling Mat for Tiling

Rev 1.0 - 13 May 2020

PRODUCT CODE - M7



EN 13967:2012

# DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) No. 305/2011

## 1. Unique Identification Code of the Product Type:

603 Tile

## 2. Type, batch or serial number of any other element allowing identification of the construction product:

See batch number and date of manufacture on the packaging

## 3. Intended Use/s:

EN 13967:2012: Flexible sheets for waterproofing

## 4. Manufacturer:

Newton Waterproofing Systems  
 (a trading name of John Newton & Company Ltd.)  
 Newton House  
 17-20 Sovereign Way  
 Tonbridge  
 Kent  
 TN9 1RH  
 01732 360095  
[www.newtonwaterproofing.co.uk](http://www.newtonwaterproofing.co.uk)

## 5. Authorised Representative:

Not Applicable

## 6. System/s of AVCP:

System 2+

## 7. Notified Body:

Harmonised standard: EN 13967:2012

Notified body SKZ TeConA GmbH (D 1213) performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance assessment and evaluation of FPC and issued the certificate of conformity of the FPC no. 4354

# NEWTON 603 TILE

## Decoupling Mat for Tiling

### 8. European Assessment Document:

Not applicable

#### EUROPEAN TECHNICAL ASSESSMENT:

Not applicable

#### TECHNICAL ASSESSMENT BODY:

Not applicable

#### NOTIFIED BODY/IES:

Not applicable

### 9. Declared Performance:

Essential Characteristics	Declared Performance	Test Standard	Harmonised Technical Standard
Water tightness, 60 kPa; 24h	Waterproof. Pass	EN 1928	DIN EN 13967:2012
Compressive strength	320 kN/m <sup>2</sup>	EN ISO 25619-2	
Tear resistance	MD - npd CMD - npd	EN 12310-1	
Tensile strength (kN/m)	MD - npd CMD - npd	EN 12311-2	
Elongation	MD - npd CMD - npd	EN 12311-2	
Compressive creep (resistance to static load)	npd	EN 13967 Annex B	
Impact resistance	npd	EN 12691-2 Method A	
Durability against ageing	npd	EN 1296 / EN 1928	
Durability against chemicals	npd	EN 1296 / EN 1928	
Fire resistance	F	EN 13501-1	
Hazardous substances	Less than limited by national regulations.		National regulations valid in EU member states.

### 10. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Warren Muschialli - Managing Director

At: Newton Waterproofing Systems  
Newton House  
17-20 Sovereign Way  
Tonbridge  
Kent  
TN9 1RH

On: 13 May 2020



# NEWTON 603 TILE

## Decoupling Mat for Tiling



Newton Waterproofing Systems  
Newton House  
17-20 Sovereign Way  
Tonbridge  
Kent TN9 1RH

603 Tile  
DIN EN 13967:2012  
1213  
Flexible sheets for waterproofing

Essential Characteristics	Declared Performance	Test Standard	Harmonised Technical Standard
Water tightness, 60 kPa; 24h	Waterproof. Pass	EN 1928	DIN EN 13967:2012
Compressive strength	320 kN/m <sup>2</sup>	EN ISO 25619-2	
Tear resistance	MD - npd CMD - npd	EN 12310-1	
Tensile strength (kN/m)	MD - npd CMD - npd	EN 12311-2	
Elongation	MD - npd CMD - npd	EN 12311-2	
Compressive creep (resistance to static load)	npd	EN 13967 Annex B	
Impact resistance	npd	EN 12691-2 Method A	
Durability against ageing	npd	EN 1296 / EN 1928	
Durability against chemicals	npd	EN 1296 / EN 1928	
Fire resistance	F	EN 13501-1	
Hazardous substances	Less than limited by national regulations.		National regulations valid in EU member states.

Newton Waterproofing Systems reserve the right to update product literature at any time. Please always refer to our [website](#) for the latest versions.