

DECLARATION OF PERFORMANCE PM3 CAVITY DRAIN MEMBRANE

PRODUCT NAME

PM3 CAVITY DRAIN MEMBRANE

INTENDED USES

Waterproofing sheet for damp proof sheets, type V

NAME, REGISTERED TRADE ADDRESS

Platinum Building Chemicals Ltd.
65 Colvilles Place,
Kelvin Industrial Estate,
East Kilbride,
G75 0PZ

AVCP

System 2+

NOTIFIED BODY

In case of the DoP concerning a construction product covered by the harmonized standard:
BS EN 13967 : 2012 + A1 : 2017

Initial type test report: British Board of Agrément test report 63213

Notified body British Board of Agrément performed the initial inspection of the manufacturing plant and of factory production control (0836-CPR-18/F440) and the continuous surveillance assessment and evaluation of FPC and issued the certificate of conformity of the FPC no.

DECLARED PERFORMANCE

Harmonised technical specification EN 13967 : 2012 + A1 : 2017

Essential Characteristics	Performance	Test Standard
Water tightness, 60 kPa; 24h	Pass	EN 1928
Resistance to tearing	MD - npd CMD - npd	EN 12310-1
Elongation (5%)	MD - npd CMD - npd	EN 12311-2
Compressive Creep (resistance to static load)	npd	EN 13967 Annex B
Impact resistance	npd	EN 12691-2 Method A
Durability against ageing	npd	EN 1296 / EN 1928
Durability against chemicals	npd	EN 1926 / EN 1928
Fire resistance	E	EN 13501-1 : 2007 + A1 : 2009
Joint tensile shear resistance		EN 12317-2
Compressive strength	250 KN	BS EN ISO 25619-2

DECLARATION OF PERFORMANCE PM3 CAVITY DRAIN MEMBRANE

DECLARATION

The performance of this product identified in points 1 and 2 is in conformity with the declared performance in point 6.

The declaration of this performance is issued under the sole responsibility of the supplier identified in point 4.

A digital copy of this Declaration of Performance can be found ****

Signed for and on behalf of the supplier by

Name:

Place and Date of Issue:

Signature: