

RIBA Insight Platon Stop - Damproofing Underlay Membrane for Concrete Floors

Support information:

- [Frequently asked questions:](#) [How does NBS Plus work?](#) | [How do I comment on my NBS Plus product data?](#) | [What is NBS Create?](#)
- [Quick links:](#) [Home](#) | [My products](#) | [How my products appear in NBS](#) | [How my products appear in NBS Create](#) | [Print this page](#)
- [Resources:](#) [NBS Newsletter](#), [Journal](#) and [eNewsletter](#) | [Terms and Conditions](#), [Disclaimer](#) and [Using the NBS Plus logo](#)
- [Contact details:](#) nbsplusproduction@thenbs.com | T: 0845 456 9594

The information below is the NBS Plus product entry for Triton Systems Platon Stop - Damproofing Underlay Membrane for Concrete Floors.

Platon Stop - Damproofing Underlay Membrane for Concrete Floors

Platon Stop provides an effective, single application damp proof underlay for wood and laminate floors laid on concrete. The tough polypropylene membrane can be laid directly onto a new concrete slab as soon as it is dry enough to walk on. The product provides three times the water resistance than film membranes and eliminates the need to install foam underlay. Platon Stop is suitable for use with conventional warm water, low voltage and certain high voltage under-floor heating systems.

Properties:

- Can be laid direct to new or existing concrete substrates.
- Suitable for use under all wood and laminate floors including glue-free systems.
- Impact sound reduction up to 19 dB.
- Exceptional stability and tear resistance.
- Construction height: 2.5 mm.

Installation:

Platon stop is fixed with damp resistant adhesive tape or a butyl rubber strip.

More about Platon Stop - Damproofing Underlay Membrane for Concrete Floors:

[As standard](#)

Platon Stop - Damproofing Underlay Membrane for Concrete Floors

- Manufacturer: Triton Systems.
- Web: www.tritonsystems.co.uk.
- Tel: +44 (0)1322 318830.
- Product reference: Platon Stop.

Add product

[top ^](#)

Guidance for Platon Stop - Damproofing Underlay Membrane for Concrete Floors from Triton Systems

More about Platon Stop - Damproofing Underlay Membrane for Concrete Floors: [As standard](#)


As standard

Roll size:

1.25 x 15 m/ 2.05 x 20 m.

Further Information

Literature:

 Additional information may be available for [Triton Systems from ribaproductselector.com](http://Triton_Systems_from_ribaproductselector.com).

Contacts:

www.tritonsystems.co.uk

technical@tritonsystems.co.uk

T: +44 (0)1322 318830

F: +44 (0)1322 524017

NBS Plus

Triton, NBS Plus Approval Site, 10 August 2012

nbsplusproduction@thenbs.com | T: 0845 456 9594