

Soudafalt**1. Identification of the substance/preparation and of the company/undertaking**

- 1.1 Identification of the substance or preparation:**
Product name: Soudafalt
- 1.2 Use of the substance or the preparation:**
Sealant
- 1.3 Company/undertaking identification:**
SODAL N.V.
Everdongenlaan 18-20
B-2300 Turnhout
Tel. : +32 14 42 42 31
Fax : +32 14 44 39 71
- 1.4 Telephone number for emergency:**
+32 14 58 45 45
Brandweerinformatiecentrum voor gevaarlijke stoffen (B.I.G.)
Technische Schoolstraat 43 A, B-2440 Geel

2. Composition/information on ingredients

Hazardous ingredients	CAS No. EINECS No.	Conc. in %	Hazard symbol	Risks (R-phrases)
naphtha, hydrodesulfurized heavy (conc. benzene < 0.1%)	64742-82-1 265-185-4	2.5 - <25	F;Xn;N	11-51/53-65-67 (1) (Labelling in compliance with CONCAWE)
asphaltbitumes	8052-42-4 232-490-9	>25	-	-
quaternary ammonium compounds, trimethyltallow alkyl, chlorides	8030-78-2 232-447-4	1 - <5	F;C	11-22-34 (1)

(1) For R-phrases in full: see heading 16

3. Hazards identification

- Flammable
- Harmful to aquatic organisms; may cause long-term adverse effects in the aquatic environment

4. First aid measures

- 4.1 Eye contact:**
- Rinse immediately with plenty of water
 - Seek medical advice
- 4.2 Skin contact:**
- Rinse immediately with plenty of water
 - If irritation persists: seek medical advice
- 4.3 After inhalation:**
- Remove the victim into fresh air
 - Seek medical advice
- 4.4 After ingestion:**
- Never give water to an unconscious person
 - Do not induce vomiting
 - Seek medical advice

5. Fire-fighting measures

- 5.1 Suitable extinguishing media:**
- Water spray
 - Polyvalent foam
 - Dry chemical powder
 - Carbon dioxide
- 5.2 Unsuitable extinguishing media:**
- Solid water jet ineffective as extinguishing medium
- 5.3 Special exposure hazards:**
- On burning: release of carbon monoxide and carbon dioxide
 - Gas/vapour flammable with air within explosion limits
- 5.4 Instructions:**
- Take account of toxic firefighting water
 - Use firefighting water moderately and contain it
- 5.5 Special protective equipment for firefighters:**
- Heat/fire exposure: compressed air/oxygen apparatus

6. Accidental release measures

- 6.1 Personal protection/precautions:**
- see heading 8.2/13
- 6.2 Environmental precautions:**
- Use appropriate containment to avoid environmental contamination
- 6.3 Methods of cleaning up:**
- Take up liquid spill into inert absorbent material e.g.: sand/earth
 - Take collected spill to competent authority
 - Wash clothing and equipment after handling

7. Handling and storage

7.1 Handling:

- Observe strict hygiene
- Avoid prolonged and repeated contact with skin
- In case of insufficient ventilation: keep naked flames/sparks away
- Do not discharge the waste into the drain
- Remove contaminated clothing immediately

7.2 Storage:

- Keep container tightly closed
- Keep away from: heat sources, ignition sources

Storage temperature : Roomtemperature
Quantity limits : N.D. **kg**
Storage life : 365 **days**
Materials for packaging :
 - suitable : plastic

7.3 Specific uses:

- See information supplied by the manufacturer

8. Exposure controls/Personal protection

8.1 Exposure limit values:

ASPHALTBITUMES:

TLV-TWA	: 0.5 I	mg/m ³	-	ppm
TLV-STEL	: -	mg/m ³	-	ppm
TLV-Ceiling	: -	mg/m ³	-	ppm
WEL-LTEL	: 5 fumes	mg/m ³	-	ppm
WEL-STEL	: 10 fumes	mg/m ³	-	ppm
MAK	: -	mg/m ³	-	ppm
MAC-TGG 8 h	: 5 rook	mg/m ³	-	
MAC-TGG 15 min.	: -	mg/m ³	-	
MAC-Ceiling	: -	mg/m ³	-	
VME-8 h	: -	mg/m ³	-	ppm
VLE-15 min.	: -	mg/m ³	-	ppm
GWBB-8 h	: 5 rook	mg/m ³	-	ppm
GWK-15 min.	: -	mg/m ³	-	ppm
Momentary value	: -	mg/m ³	-	ppm
EC	: -	mg/m ³	-	ppm
EC-STEL	: -	mg/m ³	-	ppm

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Use only in well ventilated area

8.2.1.1 Respiratory protection:

- In case of insufficient ventilation: respiratory protection with filtertype A

8.2.1.2 Hand protection:

- Chemically resistant gloves

8.2.1.3 Eye protection:

- Safety glasses

8.2.1.4 Skin protection:

- Suitable protective clothing

8.2.2 Environmental exposure controls: see heading 13

9. Physical and chemical properties

9.1 General information:

Appearance (at 20°C)	: Viscous
Odour	: Naphtha
Colour	: Black

9.2 Important health, safety and environmental information:

pH value	: N.D.	
Boiling point/boiling range	: 160	°C
Flashpoint	: 44	°C
Explosion limits	: N.D.	Vol%
Vapour pressure (at 20°C)	: 6	hPa
Vapour pressure (at 50°C)	: N.D.	hPa
Relative density (at 20°C)	: 1.3	
Water solubility	: Insoluble	
Soluble in	: Aromatic hydrocarbons, aliphatic hydrocarbons	
Relative vapour density	: N.D.	
Viscosity (at 20°C)	: 78	Pa.s
Flow time (according to ISO 2431)	: > 60	s
Partition coefficient n-octanol/water	: N.D.	
Evaporation rate		
ratio to butyl acetate	: N.D.	
ratio to ether	: N.D.	

9.3 Other information:

Melting point/melting range	: N.D.	°C
Auto-ignition point	: 210	°C
Saturation concentration	: N.D.	g/m ³

10. Stability and reactivity

10.1 Conditions to avoid/reactivity:

- Stable under normal conditions

10.2 Materials to avoid:

- Keep away from: heat sources, ignition sources

10.3 Hazardous decomposition products:

- On burning: release of carbon monoxide and carbon dioxide

11. Toxicological information

11.1 Acute toxicity:

LD50 oral rat	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LC50 inhalation rat	: N.D.	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

11.2 Chronic toxicity:

EC carc. cat. : not listed
 EC muta. cat. : not listed
 EC repr. cat. : not listed

Carcinogenicity (TLV) : not listed
 Carcinogenicity (MAC) : not listed
 Carcinogenicity (VME) : not listed
 Carcinogenicity (GWBB) : not listed

Carcinogenicity (MAK) : not listed
 Mutagenicity (MAK) : not listed
 Teratogenicity (MAK) : not listed

IARC classification : not listed

11.3 Routes of exposure: ingestion, inhalation, eye and skin

11.4 Acute effects/symptoms:

AFTER INHALATION:

EXPOSURE TO HIGH CONCENTRATIONS:

- Feeling of weakness
- Dizziness
- Headache
- Nausea
- Disturbances of consciousness

AFTER INGESTION:

- Nausea
- Irritation of the gastric/intestinal mucosa

AFTER EYE CONTACT:

- Slight irritation

ON CONTINUOUS EXPOSURE/CONTACT:

- Irritation of the eye tissue

11.5 Chronic effects:

ON CONTINUOUS EXPOSURE/CONTACT:

- Dry skin
- Skin rash/inflammation

12. Ecological information

12.1 Ecotoxicity:

- No data available

12.2 Mobility:

- Volatile organic compounds (VOC): 15 %
- Insoluble in water
- Substance sinks in water

For other physicochemical properties see section 9

12.3 Persistence and degradability:

- Biodegradation BOD₅ : N.D. % ThOD
- water : No data available
- soil : T ½ N.D. days

12.4 Bioaccumulative potential:

- log P_{ow} : N.D.
- BCF : N.D.

12.5 Other adverse effects:

- WGK : 2 (classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 17 May 1999)
- Effect on the ozone layer : Not dangerous for the ozone layer (1999/45/EC)
- Greenhouse effect : No data available
- Effect on waste water purification : No data available

13. Disposal considerations

13.1 Provisions relating to waste:

- Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 08 04 09* (waste adhesives and sealants containing organic solvents or other dangerous substances)
- Hazardous waste (91/689/EEC)

13.2 Disposal methods:

- Incinerate under surveillance
- Substance must not be discharged into the sewer
- Do not discharge into surface water

13.3 Packaging:

- Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15 01 10* (packaging containing residues of or contaminated by dangerous substances)

14. Transport information

- 14.1 Classification of the substance in compliance with UN Recommendations
 UN number : 3295
 CLASS : NOT SUBJECT
 SUB RISKS :
 PACKING :
 PROPER SHIPPING NAME :
 UN 3295, Hydrocarbons, liquid, n.o.s.(naphtha, hydrodesulfurized heavy)
- 14.2 ADR (transport by road)
 CLASS : NOT SUBJECT
 PACKING :
 DANGER LABEL TANKS :
 DANGER LABEL PACKAGES :
- 14.3 RID (transport by rail)
 CLASS : NOT SUBJECT
 PACKING :
 DANGER LABEL TANKS :
 DANGER LABEL PACKAGES :
- 14.4 ADNR (transport by inland waterways)
 CLASS : NOT SUBJECT
 PACKING :
 DANGER LABEL TANKS :
 DANGER LABEL PACKAGES :
- 14.5 IMDG (maritime transport)
 CLASS : 3
 SUB RISKS :
 PACKING : III
 MFG : -
 EMS : F-E, S-E
 MARINE POLLUTANT : -
- 14.6 ICAO (air transport)
 CLASS : 3
 SUB RISKS : -
 PACKING : III
 PACKING INSTRUCTIONS PASSENGER AIRCRAFT : 309/Y309
 PACKING INSTRUCTIONS CARGO AIRCRAFT : 310
- 14.7 Special precautions in connection with transport :
 Viscous liquid with a flash point ranging from 23°C to 60°C, which meets the conditions indicated in 2.2.3.1.5 of ADR, RID and ADNR and in 2.3.2.5 of IMDG not subject to ADR, RID and ADNR and neither to IMDG Code chapters 4.1, 5.2, 6.1

15. Regulatory information

Labelling in accordance with EC directives 67/548/EEC and 1999/45/EC

- R10 : Flammable
 R52/53 : Harmful to aquatic organisms; may cause long-term adverse effects in the aquatic environment
- S(02) : (Keep out of reach of children)
 S61 : Avoid release to the environment. Refer to special instructions/safety data sheets.

16. Other information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE
N.D. = NOT DETERMINED
***** = INTERNAL CLASSIFICATION

Exposure limits:

TLV : Threshold Limit Value - ACGIH US
OES : Occupational Exposure Standards - United Kingdom
MEL : Maximum Exposure Limits - United Kingdom
MAK : Maximale Arbeitsplatzkonzentrationen - Germany
TRK : Technische Richtkonzentrationen - Germany
MAC : Maximale aanvaarde concentratie - the Netherlands
VME : Valeurs limites de Moyenne d'Exposition - France
VLE : Valeurs limites d'Exposition à court terme - France
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium
GWK : Grenswaarde kortstondige blootstelling - Belgium
EC : Indicative occupational exposure limit values - directive 2000/39/EC

I : Inhalable fraction = **T** : Total dust = **E** : Einatembarer Aerosolanteil
R : Respirable fraction = **A** : Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit

a:	aerosol		r:	rook/Rauch	(fume)
d:	damp	(vapour)	st:	stof/Staub	(dust)
du:	dust		ve:	vezel	(fibre)
fa:	Faser	(fibre)	va:	vapour	
fi:	fibre		om:	oil mist	
fu:	fume		on:	olienevel/Ölnebel	(oil mist)
p:	poussière	(dust)	part:	particles	

Chronic toxicity:

K : List of the carcinogenic substances and processes - The Netherlands 2002

Full text of any R-phrases referred to under heading 2:

R11 : Highly flammable
R22 : Harmful if swallowed
R34 : Causes burns
R51/53 : Toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment
R65 : Harmful: may cause lung damage if swallowed
R67 : Vapours may cause drowsiness and dizziness