

Assembly Lubricant Spray

Revision: 8/03/2022

Page 1 from 1

Technical data

Basis	Mixture based on silicone oil
Consistency	Fluid
Application temperature	5 °C → 35 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

High-end silicone-oil based spray that is extremely suitable as a slide coating.

product in connection with painting.

Properties

- Improves sliding properties
- Lubricates
- Removes dirt and grease
- Protects
- Aerosol can be used in any angle (360°)

Health- and Safety Recommendations

Take the usual labour hygiene into account. Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. Dangerous. Respect the precautions for use.

Applications

- Can be applied for the assembly of plastic pipes, rubber strips and joints.
- Prevents ageing of rubber parts
- Improves the reactivation of sluggish locks, hinges, fittings and tools.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Packaging

Colour: Transparent

Packaging: 400 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

Substrates: Plastics, metals, rubbers

Application method

Application method: Fittings and pipes should be cleaned. Shake the aerosol and hold the nozzle 10 - 20 cm from the subject. Spray on the parts and assemble. When used as a lubricant for hinges, hold the nozzle close to the part. Carefully press the valve and let the silicone-oil work for a while. Do not use this

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.