

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Cockpit Maintenance Spray
Type of product : Detergent
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use, Professional use
Use of the substance/mixture : Cleaning agent

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Soudal N.V.
Everdongenlaan 18-20
2300 Turnhout
Belgium
T +32 14 42 42 31 - F +32 14 42 65 14
sds@soudal.com - www.Soudal.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Toxic to aquatic life with long lasting effects.

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, hydrocarbons, C6, isoalkanes, < 5% n-hexane, n-hexane

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P391 - Collect spillage.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
butane (106-97-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane substance with national workplace exposure limit(s) (BE)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0	$\geq 50 - < 75$	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	EC-No.: 927-510-4 REACH-no: 01-2119475515-33	≥ 10 – < 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411
propane substance with national workplace exposure limit(s) (BE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5	≥ 10 – < 25	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
paraffin oil substance with national workplace exposure limit(s) (BE)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 01-2119487078-27	< 10	Asp. Tox. 1, H304
hydrocarbons, C6, isoalkanes, < 5% n-hexane	EC-No.: 931-254-9 REACH-no: 01-2119484651-34	≥ 1 – < 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butane (106-97-8)	
Belgium - Occupational Exposure Limits	
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan
OEL STEL	2370 mg/m ³
OEL STEL [ppm]	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane (74-98-6)	
Belgium - Occupational Exposure Limits	
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)
OEL TWA [ppm]	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
paraffin oil (8042-47-5)	
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	300 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2085 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	149 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	447 mg/m ³
Long-term - systemic effects, dermal	149 mg/kg bodyweight/day
hydrocarbons, C6, isoalkanes, < 5% n-hexane	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	13964 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	5306 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	1301 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1131 mg/m ³
Long-term - systemic effects, dermal	1377 mg/kg bodyweight/day

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 89,5887499999998

9.2.2. Other safety characteristics

VOC content : 91,9 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	> 23,3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
paraffin oil (8042-47-5)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Skin corrosion/irritation	: Causes skin irritation.
butane (106-97-8)	
pH	No data available in the literature

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane (74-98-6)	
pH	No data available in the literature
paraffin oil (8042-47-5)	
pH	Not applicable
Serious eye damage/irritation	: Not classified
butane (106-97-8)	
pH	No data available in the literature
propane (74-98-6)	
pH	No data available in the literature
paraffin oil (8042-47-5)	
pH	Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
STOT-single exposure	May cause drowsiness or dizziness.
hydrocarbons, C6, isoalkanes, < 5% n-hexane	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
LOAEC (inhalation, rat, vapour, 90 days)	16,6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapour, 90 days)	3,3 mg/l air Animal: rat, Animal sex: male
paraffin oil (8042-47-5)	
NOAEL (oral, rat, 90 days)	≥ 1200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Aspiration hazard	: Not classified
Cockpit Maintenance Spray	
Vaporizer	Aerosol
butane (106-97-8)	
Viscosity, kinematic	No data available in the literature
propane (74-98-6)	
Viscosity, kinematic	No data available in the literature
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	
Viscosity, kinematic	0,67 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
hydrocarbons, C6, isoalkanes, < 5% n-hexane	
Viscosity, kinematic	0,46 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
paraffin oil (8042-47-5)	
Viscosity, kinematic	31 mm ² /s (40 °C)

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.
Not rapidly degradable

butane (106-97-8)

LC50 - Fish [1]	24,11 mg/l (ECOSAR, 96 h, Pisces, Fresh water, QSAR)
EC50 96h - Algae [1]	7,71 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

propane (74-98-6)

LC50 - Fish [1]	49,9 mg/l (96 h, Pisces, Fresh water, QSAR, Estimated value)
EC50 96h - Algae [1]	11,89 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

paraffin oil (8042-47-5)

LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
-----------------	--

12.2. Persistence and degradability

butane (106-97-8)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

propane (74-98-6)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

paraffin oil (8042-47-5)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

12.3. Bioaccumulative potential

butane (106-97-8)

Partition coefficient n-octanol/water (Log Pow)	2,8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

propane (74-98-6)

Partition coefficient n-octanol/water (Log Pow)	1,09 – 2,8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

paraffin oil (8042-47-5)

Partition coefficient n-octanol/water (Log Pow)	5,6 – 25 (Calculated, EPIWIN)
---	-------------------------------

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

paraffin oil (8042-47-5)

Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
---------------------------	---

12.4. Mobility in soil

propane (74-98-6)

Surface tension	No data available in the literature
-----------------	-------------------------------------

Ecology - soil	Not applicable (gas).
----------------	-----------------------

paraffin oil (8042-47-5)

Surface tension	0,027 – 0,035 N/m
-----------------	-------------------

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 16 05 04* - gases in pressure containers (including halons) containing dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F
Special provisions (RID) : 190, 327, 344, 625
Limited quantities (RID) : 1L
Excepted quantities (RID) : E0
Packing instructions (RID) : P207, LP200
Special packing provisions (RID) : PP87, RR6, L2
Mixed packing provisions (RID) : MP9
Transport category (RID) : 2
Special provisions for carriage – Packages (RID) : W14
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12
Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)

Reference code	Applicable on	Entry title or description
3(a)	Cockpit Maintenance Spray ; hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ; hydrocarbons, C6, isoalkanes, < 5% n-hexane	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Cockpit Maintenance Spray ; hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ; hydrocarbons, C6, isoalkanes, < 5% n-hexane ; paraffin oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Cockpit Maintenance Spray ; hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ; hydrocarbons, C6, isoalkanes, < 5% n-hexane	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 91,9 %

Detergent Regulation (648/2004)

Labelling of contents	
Component	%
aliphatic hydrocarbons	≥30%
perfumes	

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method

Cockpit Maintenance Spray

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aquatic Chronic 2	H411	Calculation method
-------------------	------	--------------------

Safety Data Sheet (SDS), EU-20221

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.