

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

Soudal Trade Gap Filler with Genius Gun

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Soudal Trade Gap Filler with Genius Gun

Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

polyurethane

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

SOUDAL N.V. Everdongenlaan 18-20

B-2300 Turnhout

3 +32 14 42 42 31 +32 14 42 65 14

msds@soudal.com

Manufacturer of the product

SOUDAL N.V.

Everdongenlaan 18-20

B-2300 Turnhout

3 +32 14 42 42 31 +32 14 42 65 14

msds@soudal.com

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	categ <mark>ory 1</mark>	H222: Extremely flammable aerosol.
Aerosol	categ <mark>ory 1</mark>	H229: Pressurised container: May burst if heated.
Carc.	category 2	H351: Suspected of causing cancer.
Resp. Sens.	categ <mark>ory 1</mark>	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	categ <mark>ory 1</mark>	H317: May cause an allergic skin reaction.
Acute Tox.	categ <mark>ory 4</mark>	H332: Harmful if inhaled.
STOT RE	category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Skin Irrit.	category 2	H315: Causes skin irritation.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	categ <mark>ory 3</mark>	H335: May cause respiratory irritation.

2.2. Label elements







Contains: polymethylene polyphenyl isocyanate.

Signal word

H-statements H222

H229 Pressurised container: May burst if heated.

Extremely flammable aerosol.

H351 Suspected of causing cancer.

Danger

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

http://www.big.be © BIG vzw

Reason for revision: 3

Revision number: 0603 Product number: 36142

Publication date: 2001-10-17 Date of revision: 2018-01-08

1/15

H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
P-statements	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

		CAS No EC No		Conc. (C)	Classification according to CLP	Note	Remark
dimethyl ether 01-2119472128-37		115-10-6 204-065-8		1% <c<10%< th=""><th>Flam. Gas 1; H220 Press. Gas - Liquefied gas;</th><th>(1)(2)(10)</th><th>Propellant</th></c<10%<>	Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant
isobutane 01-2119485395-27		75-28-5 200-857-2		1% <c<10%< td=""><td>Flam. Gas 1; H220 Press. Gas - Liquefied gas;</td><td>(1)(2)(10)</td><td>Propellant</td></c<10%<>	Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant
propane 01-2119486944-21		74-98-6 200-827-9		1% <c<10%< td=""><td>Flam. Gas 1; H220 Press. Gas - Liquefied gas;</td><td>(1)(2)(10)</td><td>Propellant</td></c<10%<>	Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant
reaction mass of tris(2-chloropr tris(2-chloro-1-methylethyl) pho acid, bis(2-chloro-1-methylethyl and phosphoric acid, 2-chloro-1 chloropropyl) ester 01-2119486772-26	osphate and phosphoric 2 chloropropyl ester			10% <c<20%< td=""><td>Acute Tox. 4; H302</td><td>(1)(10)</td><td>Constituent</td></c<20%<>	Acute Tox. 4; H302	(1)(10)	Constituent
polymethylene polyphenyl isocy	vanate	9016-87-9			Carc. 2; H351 Resp. Sens. 1; H334 Skin Sens. 1; H317 Acute Tox. 4; H332 STOT RE 2; H373 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	(1)(2)(8)(10)(18)	Constituent
(1,3-butadiene, conc<0.1%)							

- (1) For H-statements in full: see heading 16
- (2) Substance with a Community workplace exposure limit
- (8) Specific concentration limits, see heading 16
- (10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006
- (18) Polymethylene polyphenyl isocyanate, contains > 0.1% MDI-isomers

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

Reason for revision: 3	Publication date: 2001-10-17
	Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 2 / 15

After skin contact:

Wash immediately with lots of water. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Runny nose. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible inflammation of the respiratory tract. Risk of lung oedema. Respiratory difficulties.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue. Lacrimation.

After ingestion:

Not applicable.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher.

5.1.2 Unsuitable extinguishing media:

Small fire: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), Foam.

Major fire: Water (water can be used to control jet flame), Foam.

5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide).

Pressurised container: May burst if heated. May polymerize on exposure to temperature rise. On heating: release of toxic/combustible gases/vapours (hydrogen cyanide).

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosion proof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Dam up the liquid spill. Use appropriate containment to avoid environmental contamination.

6.3. Methods and material for containment and cleaning up

Allow product to solidify and remove it by mechanical means. Carefully collect the spill/leftovers. Clean (treat) contaminated surfaces with acetone. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

Reason for revision: 3 Publication date: 2001-10-17 Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 3 / 15

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Fireproof storeroom. Ventilation at floor level. Meet the legal requirements. Max. storage time: 1 year(s).

7.2.2 Keep away from:

Heat sources, ignition sources, (strong) acids, (strong) bases, amines.

7.2.3 Suitable packaging material:

Aerosol

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

:U		
Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m³
Belgium		
1,4'-Diisocyanate de dip <mark>hénylméthane (MDI)</mark>	Time-weighted average exposure limit 8 h	0.005 ppm
	Time-weighted average exposure limit 8 h	0.052 mg/m ³
Hydrocarbures aliphatiq <mark>ues sous forme gazeuse : (Alcanes C1-</mark> C4)	Time-weighted average exposure limit 8 h	1000 ppm
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m³
The Netherlands		
Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	496 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m³
	Short time value (Public occupational exposure limit value)	783 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m ³
France		
1,4'-Diisocyanate de diph <mark>énylméthane</mark>	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	0.01 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	0.1 mg/m ³
	Short time value (VL: Valeur non réglementaire indicative)	0.02 ppm
	Short time value (VL: Valeur non réglementaire indicative)	0.2 mg/m ³
Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m³
Germany		
1,4'-Methylendiphenyldii <mark>socyanat</mark>	Time-weighted average exposure limit 8 h (TRGS 900)	0.05 mg/m ³
Dimethylether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m ³
sobutan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m ³
oMDI (als MDI berechnet <mark>)</mark>	Time-weighted average exposure limit 8 h (TRGS 900)	0.05 mg/m³

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 4/15

Propan		Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
		Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m³
UK			
Dimethyl ether		Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
		Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m³
		Short time value (Workplace exposure limit (EH40/2005))	500 ppm
		Short time value (Workplace exposure limit (EH40/2005))	958 mg/m³
Isocyanates, all (as -NCO)	Except methyl isocyanate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	0.02 mg/m ³
		Short time value (Workplace exposure limit (EH40/2005))	0.07 mg/m ³

USA (TLV-ACGIH)

Butane, all isomers	Short time value (TLV - Adopted Value)	1000 ppm
Methylene bisphenyl isoc <mark>yanate (MDI)</mark>	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	0.005 ppm

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

Product name		Test	Number	
Isocyanates		NIOSH	5521	
Isocyanates		NIOSH	5522	

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

ster and phosphone deld) = emer	of methylethyl bis(2 chiolopropy) ester		
Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	5.82 mg/m³	
	Acute systemic effects inhalation	22.4 mg/m ³	
	Long-term systemic effects dermal	2.08 mg/kg bw/day	
	Acute systemic effects dermal	8 mg/kg bw/day	

DNEL/DMEL - General population

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	1.46 mg/m³	
	Acute systemic effects inhalation	11.2 mg/m³	
	Long-term systemic effects dermal	1.04 mg/kg bw/day	
	Acute systemic effects dermal	4 mg/kg bw/day	
	Long-term systemic effects oral	0.52 mg/kg bw/day	

PNEC

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Compartments	Value	Remark
Fresh water	0.64 mg/l	
Aqua (intermittent releases)	0.51 mg/l	
Marine water	0.064 mg/l	
STP	7.84 mg/l	
Fresh water sediment	13.4 mg/kg sediment dw	
Marine water sediment	1.34 mg/kg sediment dw	
Soil	1.7 mg/kg soil dw	
Oral	11.6 mg/kg food	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 5 / 15

Gloves.

0.0100					
Materials	Bre	akthroug	h time	Thickness	
LDPE (Low Density Poly E	thylene) > 10	0 minutes		0.025 mm	

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form		Aerosol					
Odour		Characteristic odour					
Odour threshold		No data available					
Colour		Variable in colour, depending on the composition					
Particle size		No data available					
Explosion limits		No data available					
Flammability		Extremely flammable aerosol.					
Log Kow		Not applicable (mixture)					
Dynamic viscosity		No data available					
Kinematic viscosity		No data available					
Melting point		No data available					
Boiling point		No data available					
Evaporation rate		No data available					
Relative vapour density		>1					
Vapour pressure		No data available					
Solubility		Water ; insoluble					
Relative density		No data available					
Decomposition tempera	ture	No data available					
Auto-ignition temperatu	re	No data available					
Flash point		No data available					
Explosive properties		No chemical group associated with explosive properties					
Oxidising properties		No chemical group associated with oxidising properties					
рН		No data available					

9.2. Other information

Surface tension	No data available
Absolute density	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Unstable on exposure to heat.

10.3. Possibility of hazardous reactions

May polymerize with many compounds e.g.: (strong) bases and amines. Reacts violently with (some) acids/bases.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

(strong) acids, (strong) bases, amines.

10.6. Hazardous decomposition products

On heating: release of toxic/combustible gases/vapours (hydrogen cyanide). On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide).

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Revision number: 36142 6 / 15

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

Classification is based on the relevant ingredients

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	EU Method B.1 tris	632 mg/kg bw		Rat (female)	Experimental value	
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rat (male/female)	Experimental value	
Inhalation (aerosol)	LC50	OECD 403	> 7 mg/l	4 h	Rat (male/female)	Experimental value	

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50		> 10000 mg/kg		Rat	Literature study	
Dermal	LD50		> 5000 mg/kg		Rabbit	Literature study	
Inhalation (vapours)	LD50		<mark>10 mg/l -</mark> 20 mg/l	4 h	Rat	Literature study	
Inhalation			category 4			Literature study	

Conclusion

Harmful if inhaled.

Not classified as acute toxic in contact with skin

Not classified as acute toxic if swallowed

Corrosion/irritation

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

Classification is based on the relevant ingredients

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Not irrit <mark>ating</mark>	OECD 405	24 h	7 days	Rabbit	Experimental value	
Skin	Not irrit <mark>ating</mark>	OECD 404	4 h	7 days	Rabbit	Experimental value	

polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Time point	Value determination	Remark
*	Irritating; category 2				Literature study	
	Irritating; category 2				Literature study	
	Irritating; STOT SE cat.3				Literature study	

Conclusion

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

Respiratory or skin sensitisation

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

Classification is based on the relevant ingredients

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Route of exposure	Result	Method	Observation time point	Species	Value determination	Remark
Skin	Not sensi <mark>tizing</mark>	OECD 429		Mouse (female)	Experimental value	

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 7 / 15

polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	•	Observation time point	Species	Value determination	Remark
Skin	Sensitizin <mark>g;</mark> category 1					Literature study	
Inhalation	Sensitizi <mark>ng;</mark> category 1					Literature study	

Conclusion

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Specific target organ toxicity

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

Classification is based on the relevant ingredients

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Route of exposure	Parame	ter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral (diet)	NOAEL			171 mg/kg bw/day		No effect	13 weeks (daily)	, ,	Experimental value
Oral (diet)	LOAEL			52 mg/kg bw/day	Liver	Weight gain	13 weeks (daily)		Experimental value
Inhalation (vapours)	Dose lev	/el		0.586 mg/l air		No effect			Experimental value

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Value determination
Inhalation			STOT RE cat.2				Literature study

Conclusion

May cause damage to organs through prolonged or repeated exposure if inhaled.

Not classified as sub-chronically toxic if swallowed

Mutagenicity (in vitro)

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic	OECD 482	Rat liver cells		Experimental value
activation, negative without				
metabolic activation				
Negative without metabolic	OECD 476	Mouse (lymphoma L5178Y		Experimental value
activation, positive with		cells)		
metabolic activation				

Mutagenicity (in vivo)

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Result	Method	Method Exposure time T		Organ	Value determination
Negative	OECD 474		Mouse (male/female)	Bone marrow	Experimental value

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

Classification is based on the relevant ingredients

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 8 / 15

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	. 3	Value determination
Inhalation								Data waiving
Dermal								Data waiving
Oral								Data waiving

polymethylene polyphenyl isocyanate

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Unknown			category 2					Literature study

Conclusion

Suspected of causing cancer.

Reproductive toxicity

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

	Parameter	Method	Value	Exposure time	Species	Effect	9	Value determination
Developmental toxicity	LOAEL		99 mg/kg bw/day		Rat (female)	Embryotoxicity		Experimental value
Effects on fertility	LOAEL		99 mg/kg bw/day		Rat (male/female)		Female reproductive organ	Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

Chronic effects from short and long-term exposure

Soudal Trade Gap Filler with Genius Gun

Body temperature rise. Tremor. Feeling of weakness. Headache. Skin rash/inflammation. May stain the skin. Dry skin. Risk of pneumonia.

SECTION 12: Ecological information

12.1. Toxicity

Soudal Trade Gap Filler with Genius Gun

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Other	56.2 mg/l	96 h	Brachydanio rerio	Static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	LC50		131 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquation plants	ErC50	OECD 201	82 mg/l	72 h	Pseudokirchnerie lla subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC	OECD 202	32 mg/l	21 day(s)		Semi-static system	Fresh water	Experimental value; GLP
Toxicity aquatic micro- organisms	EC50	ISO 8192	784 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; GLP

polymethylene polyphenyl isocyanate

	Parameter	Method	Value	Duration	Species	 Fresh/salt water	Value determination
Acute toxicity other aquatic organisms	LC50		> 1000 mg/l	96 h			Literature study
Toxicity aquatic micro- organisms	EC50	OECD 209	> 100 mg/l		Activated sludge		Literature study

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 9 / 15

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Biodegradation water

Method	Value		Duration	Value determination
OECD 301E: Modified OECD Screening Test	14 %; GLP		28 day(s)	Experimental value
Phototransformation air (DT50 air)				

Method		Value		Conc. OH-radicals		Value determination	
AOPWIN v1.92	8.0	.6 h		500000 /cm³		Calculated value	
Diadogradation sail							

Biodegradation soil

Method	Value	Duration	Value determination
			Data waiving

Half-life water (t1/2 water)

Method	V	alue	Primary degradation/mineralisation	Value determination
EU Method C.7	>	1 year(s)	Primary degradation	Experimental value

polymethylene polyphenyl isocyanate

Biodegradation water

Method	Value	Duration	Value determination
OECD 302C: Inherent Biodegradability:	< 60 %		Experimental value
Modified MITI Test (II)			

Conclusion

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

Soudal Trade Gap Filler with Genius Gun

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	0.8 - 14; Fresh	6 week(s)	Cyprinus carpio	Experimental value

Loa Kow

Method	Remark	Value	Temperature	Value determination
EU Method A.8		2.68	30 °C	Experimental value

polymethylene polyphenyl isocyanate

BCF fishes

	Parameter	Metho	d	Value	Dur	ation	Species	Value determination
	BCF			1			Pisces	Literature study
17	oa Kow							

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

12.4. Mobility in soil

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

(log) Koc

Parameter		Method	Value	Value determination
log Koc		EU Method C.19	2.76	Experimental value

Percent distribution

Method	Fraction air		Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.01 %	0 %	3.55 %	3.52 %	92.89 %	Read-across

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Reason for revision: 3 Publication date: 2001-10-17 Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 10 / 15

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

Soudal Trade Gap Filler with Genius Gun

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 05 01* (wastes not otherwise specified in 08: waste isocyanates).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Recycle/reuse. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information Road (ADR) 14.1. UN number UN number 1950 14.2. UN proper shipping name Proper shipping name Aerosols 14.3. Transport hazard class(es) Hazard identification number Class Classification code 5F 14.4. Packing group Packing group Labels 2.1 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions 190 Special provisions 327 Special provisions 344 Special provisions 625 Limited quantities Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) Rail (RID) 14.1. UN number UN number 1950 14.2. UN proper shipping name Aerosols Proper shipping name 14.3. Transport hazard class(es) Hazard identification number 23 Class Classification code 5F 14.4. Packing group Packing group 2.1 14.5. Environmental hazards Environmentally hazardous substance mark no Reason for revision: 3 Publication date: 2001-10-17

Revision number: 36142 11/15

Date of revision: 2018-01-08

Soudal Trade Gap Filler with Genius Gun 14.6. Special precautions for user Special provisions 190 327 Special provisions Special provisions 344 Special provisions 625 Combination packagings: not more than 1 liter per inner packaging for Limited quantities liquids. A package shall not weigh more than 30 kg. (gross mass) Inland waterways (ADN) 14.1. UN number UN number 1950 14.2. UN proper shipping name Proper shipping name Aerosols 14.3. Transport hazard class(es) Class Classification code 5F 14.4. Packing group Packing group Labels 2.1 14.5. Environmental hazards Environmentally hazardous substance mark no 14.6. Special precautions for user 190 Special provisions 327 Special provisions 344 Special provisions Special provisions 625 Limited quantities Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) Sea (IMDG/IMSBC) 14.1. UN number UN number 1950 14.2. UN proper shipping name Proper shipping name Aerosols 14.3. Transport hazard class(es) Class 2.1 14.4. Packing group Packing group Labels 2.1 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark no 14.6. Special precautions for user 63 Special provisions Special provisions 190 Special provisions 277 Special provisions 327 Special provisions 344 Special provisions 381 Special provisions Limited quantities Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Annex II of MARPOL 73/78 Not applicable Air (ICAO-TI/IATA-DGR) 14.1. UN number UN number 1950 14.2. UN proper shipping name Aerosols, flammable Proper shipping name 14.3. Transport hazard class(es) Class 2.1 14.4. Packing group Packing group Labels 2.1 14.5. Environmental hazards

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Environmentally hazardous substance mark

14.6. Special precautions for user Special provisions

Revision number: 36142 12 / 15

A145

Special provisions	A167	
Special provisions	A802	
Limited quantities: maximum net quantity per packaging	30 kg G	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content		Remark	
14 % - 18 %			

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	ngerous	s substances, mixtures and articles.	(., ,
		Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· reaction mass of tris(2-chloropropy phosphate and tris(2-chloro-1-methy phosphate and phosphoric acid, bis(3-chloro-1-methylethyl) 2-chloropropy and phosphoric acid, 2-chloro-1-met bis(2-chloropropyl) ester · polymethylene polyphenyl isocyana	vlethyl) 2- I ester hylethyl ite	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) Iamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. 6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordan
· polymethylene polyphenyl isocyana		Methylenediphenyl diisocyanate (MDI) including the following specific isomers: 4,4'-Methylenediphenyl diisocyanate; 2,4'-Methylenediphenyl diisocyanate; 2,2'-Methylenediphenyl diisocyanate	 Shall not be placed on the market after 27 December 2010, as a constituent of mixtures in concentrations equal to or greater than 0,1 % by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging: (a) contains protective gloves which comply with the requirements of Council Directive 89/686/EEC; (b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures:
National legislation Belgium Soudal Trade Gap Filler w		nius Gun	
No data available	idi Gel	ildo Guit	
National legislation The Net	herland	<u>ds</u>	

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Soudal Trade Gap Filler with Genius Gun

Waterbezwaarlijkheid

Revision number: 0603 Product number: 36142 13 / 15

National legislation France

Soudal Trade Gap Filler with Genius Gun

No data available

polymethylene polyphenyl isocyanate

Catégorie cancérogène 4,4'-Diisocyanate de diphénylméthane; C2

National legislation Germany

Soudal Trade Gap Filler with Genius Gun

UGK

1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4) and Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) of 18 April 2017

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl

ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

ester and phosphoric acit	a, Z-CITIC	oro-1-metriyletriyi bis(2-triloropropyi) ester				
TA-Luft		5.2.5				
polymethylene polyphen	yl isocya	anate				
TA-Luft	TA-Luft 5.2.5; I					
TRGS900 - Risiko der		4,4'-Methylendiphenyldiisocyanat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes				
Fruchtschädigung		und des biologischen Grenzwertes nicht befürchtet zu werden				
		pMDI (als MDI berechnet); Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des				
		<mark>biologischen Grenzwertes nich</mark> t befürchtet zu werden				
Sensibilisierende Stoffe		4,4'-Methylendiphenyldiisocyanat; Sah; Atemwegssensibilisierende Stoffe Und Hautsensibilisierende Stoffe, an beiden				
		Zielorganen Allergien auslösende				
		pMDI (als MDI berechnet); Sa; Atemwegssensibilisierende Stoffe				
TRGS905 - Krebserzeug	end	Techn. ("Polymeres") MDI (pMDI) (in Form atembarer Aerosole, A-Fraktion); 2				
TRGS905 - Erbgutverän	dernd	Techn. ("Polymeres") MDI (pMDI) (in Form atembarer Aerosole, A-Fraktion); -				
TRGS905 -		Techn. ("Polymeres") MDI (pMDI) (in Form atembarer Aerosole, A-Fraktion); -				
Fruchtbarkeitsgefährdend						
TRGS905 - Fruchtschädi	igend	Techn. ("Polymeres") MDI (pMDI) (in Form atembarer Aerosole, A-Fraktion); -				
Hautresorptive Stoffe		<mark>4,4'-Methylendiphenyldiisocya</mark> nat; H; Hautresorptiv				
		pMDI (als MDI berechnet); H; Hautresorptiv				

National legislation United Kingdom

Soudal Trade Gap Filler with Genius Gun

No data available

polymethylene polyphenyl isocyanate

Skin Sensitisation	Isocyanates, all (as -NCO) Except methyl isocyanate; Sen
Respiratory sensitisation	Isocyanates, all (as -NCO) Except methyl isocyanate; Sen

Other relevant data

Soudal Trade Gap Filler with Genius Gun

No data available

polymethylene polyphenyl isocyanate

IARC - classification 3; Polymethylene polyphenyl isocyanate

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H-statements referred to under heading 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

(*) INTERNAL CLASSIFICATION BY BIG

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 14/15

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

Specific concentration limits CLP

polymethylene polyphen <mark>yl isocyanate</mark>	C ≥ 5 %	Eye Irrit 2;H319	analogous to Annex VI
	C ≥ 5 %	Skin Irrit 2;H315	analogous to Annex VI
	C ≥ 0.1 %	Resp Sens 1;H334	analogous to Annex VI
	C ≥ 5 %	STOT SE 3;H335	analogous to Annex VI

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet has been elaborated for use within the European Union, Switzerland, Iceland, Norway and Lichtenstein. It may be consulted in other countries, where local legislation with regards to the set-up of safety data sheets will take precedence. It is your obligation to verify and apply such local legislation. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3 Publication date: 2001-10-17
Date of revision: 2018-01-08

Revision number: 0603 Product number: 36142 15 / 15