

Rim Cleaner

Revision: 8/03/2022

Page 1 from 1

Technical data

Basis	Waterbased cleaning foam
Consistency	Fluid
Application temperature	5 °C → 35 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

High-quality concentrated cleaning foamspray in order to get clean rims, providing a long lasting cleaning effect.

Properties

- Cleans and protects.
- Does not drip
- Not staining
- Extreme dirt resistance.
- High cleaning properties.

Applications

- Exclusive non-drip and no color change effects, ensuring a complete removal of any dirt accumulated on the wheel surfaces.
- Suited for aluminum and plastic rims providing excellent cleansing properties because of the vertical stability when applied.

Packaging

Colour: Transparent

Packaging: 400 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

Substrates: Plastics and metals

Application method

Application method: Shake before use and apply generously and allow to take effect. Remove the dirt with a wheel cleaner brush

and rinse thoroughly.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. Dangerous. Respect the precautions for use.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.