

Ultra Repair Adhesive

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Ultra Repair Adhesive
 Registration number REACH : Not applicable (mixture)
 Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Adhesive

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

SODAL N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 ☐ +32 14 42 65 14
 msds@soudal.com

Manufacturer of the product

SODAL N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 ☐ +32 14 42 65 14
 msds@soudal.com

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):
 +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

2.2. Label elements

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

2.3. Other hazards

No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
trimethoxyvinylsilane 01-2119513215-52	2768-02-7 220-449-8	1%<C<10%	Flam. Liq. 3; H226 Acute Tox. 4; H332 STOT RE 2; H373	(1)(10)	Constituent
3-(trimethoxysilyl)propylamine 01-2119510159-45	13822-56-5 237-511-5	1%<C<3%	Eye Dam. 1; H318 Skin Irrit. 2; H315	(1)(10)	Constituent

(1) For H-statements in full: see heading 16

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Ultra Repair Adhesive

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Rinse with water. Soap may be used. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

No effects known.

After eye contact:

No effects known.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Adapt extinguishing media to the environment for surrounding fires.

5.1.2 Unsuitable extinguishing media:

Not applicable.

5.2. Special hazards arising from the substance or mixture

Upon combustion: formation of CO, CO₂ and small quantities of nitrous vapours.

5.3. Advice for firefighters

5.3.1 Instructions:

No specific fire-fighting instructions required.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released product. Use appropriate containment to avoid environmental contamination.

6.3. Methods and material for containment and cleaning up

Cover spill with inert material, e.g.: sand, earth, vermiculite. Scoop solid spill into closing containers. Clean contaminated surfaces with an excess of water.

Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

Ultra Repair Adhesive

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Observe normal hygiene standards. Keep container tightly closed. Remove contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Meet the legal requirements. Store at room temperature. Max. storage time: 1 year(s).

7.2.2 Keep away from:

No data available.

7.2.3 Suitable packaging material:

Synthetic material.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

trimethoxyvinylsilane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.6 mg/m ³	
	Acute systemic effects inhalation	2.6 mg/m ³	
	Long-term systemic effects dermal	0.2 mg/kg bw/day	
	Acute systemic effects dermal	0.2 mg/kg bw/day	

3-(trimethoxysilyl)propylamine

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	58 mg/m ³	
	Long-term systemic effects dermal	8.3 mg/kg bw/day	

DNEL/DMEL - General population

trimethoxyvinylsilane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	0.7 mg/m ³	
	Acute systemic effects inhalation	0.7 mg/m ³	
	Long-term systemic effects dermal	0.1 mg/kg bw/day	
	Acute systemic effects dermal	0.1 mg/kg bw/day	
	Long-term systemic effects oral	0.1 mg/kg bw/day	

3-(trimethoxysilyl)propylamine

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	17 mg/m ³	
	Long-term systemic effects dermal	5 mg/kg bw/day	
	Long-term systemic effects oral	5 mg/kg bw/day	

PNEC

trimethoxyvinylsilane

Compartments	Value	Remark
Fresh water	0.36 mg/l	
Marine water	0.036 mg/l	
STP	6.6 mg/l	
Fresh water sediment	1.3 mg/kg sediment dw	
Marine water sediment	0.13 mg/kg sediment dw	
Soil	0.055 mg/kg soil dw	

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

3 / 12

Ultra Repair Adhesive

3-(trimethoxysilyl)propylamine

Compartments	Value	Remark
Fresh water	0.33 mg/l	
Marine water	0.033 mg/l	
Aqua (intermittent releases)	3.3 mg/l	
STP	13 mg/l	
Fresh water sediment	1.2 mg/kg sediment dw	
Marine water sediment	0.12 mg/kg sediment dw	
Soil	0.045 mg/kg soil dw	
Oral	44.4 mg/kg food	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection:

Respiratory protection not required in normal conditions.

b) Hand protection:

Gloves.

c) Eye protection:

Eye protection not required in normal conditions.

d) Skin protection:

Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Paste
Odour	Mild odour Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	No data available
Explosion limits	No data available
Flammability	Non combustible
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Relative vapour density	No data available
Vapour pressure	No data available
Solubility	Water ; insoluble Organic solvents ; soluble
Relative density	1.08 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2. Other information

Absolute density	1080 kg/m ³ ; 20 °C
------------------	--------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under normal conditions.

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

4 / 12

Ultra Repair Adhesive

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: formation of CO, CO₂ and small quantities of nitrous vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

Ultra Repair Adhesive

No (test) data on the mixture available

Judgement is based on the relevant ingredients

trimethoxyvinylsilane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	7120 mg/kg bw - 7236 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	3259 mg/kg bw	24 h	Rabbit (female)	Converted value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	16.81 mg/l	4 h	Rat (male/female)	Experimental value	

3-(trimethoxysilyl)propylamine

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	2.970 ml/kg bw		Rat (male)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	11.3 ml/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)	LC50	OECD 403	> 5 ppm	6 h	Rat (male)	Read-across	
Inhalation (vapours)	LC50	OECD 403	> 16 ppm	6 h	Rat (female)	Read-across	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

Ultra Repair Adhesive

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
	Not irritating	OECD 437				Experimental value	

In the light of practical experience, the classification for this mixture is less stringent than the one based on the calculation set out

trimethoxyvinylsilane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405	24 h	1; 24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating		24 h	24; 48; 72 hours	Rabbit	Experimental value	

3-(trimethoxysilyl)propylamine

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	
Skin	Irritating	OECD 404	3 minutes - 240 minutes	1; 24; 48; 72; 168 hours	Rat	Calculated value	

Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

5 / 12

Ultra Repair Adhesive

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

Ultra Repair Adhesive

No (test) data on the mixture available

Judgement is based on the relevant ingredients

trimethoxyvinylsilane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406		24; 48 hours	Guinea pig (male/female)	Experimental value	

3-(trimethoxysilyl)propylamine

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406	72 h	24; 48 hours	Guinea pig (male/female)	Experimental value	

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

Ultra Repair Adhesive

No (test) data on the mixture available

Judgement is based on the relevant ingredients

trimethoxyvinylsilane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	LOAEL	OECD 422	62.5 mg/kg bw/day	Bladder	Histopathological changes		Rat (male)	Experimental value
Inhalation (vapours)	NOAEC	Subchronic toxicity test	10 ppm		No effect	14 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value

3-(trimethoxysilyl)propylamine

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	LOAEL	OECD 408	600 mg/kg bw/day	Liver	Clinical signs; mortality; body weight; food consumption	92 day(s)	Rat (male/female)	Read-across
Oral (stomach tube)	NOAEL	OECD 408	200 mg/kg bw/day	Liver	No effect	92 day(s)	Rat (male/female)	Read-across
Inhalation (aerosol)	IRT (inhalation risk test)	Equivalent to OECD 412	147 mg/m ³ air	Lungs	Lesions in larynx, trachea and lung	4 weeks (6h/day, 5 days/week)	Rat (male)	Read-across

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

Ultra Repair Adhesive

No (test) data on the mixture available

trimethoxyvinylsilane

Result	Method	Test substrate	Effect	Value determination
Positive with metabolic activation, positive without metabolic activation	OECD 473	CHL/IU cells	Chromosome aberrations	Experimental value

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

6 / 12

Ultra Repair Adhesive

3-(trimethoxysilyl)propylamine

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	OECD 476	Chinese hamster ovary (CHO)	No effect	Read-across
Negative with metabolic activation, negative without metabolic activation	OECD 473	Chinese hamster lung fibroblasts (V79)	No effect	Read-across
Negative with metabolic activation, negative without metabolic activation	OECD 471	Escherichia coli	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

Mutagenicity (in vivo)

Ultra Repair Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

trimethoxyvinylsilane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	EPA 560/6-83-001		Mouse (male/female)		Experimental value

3-(trimethoxysilyl)propylamine

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 474		Mouse (male/female)	Bone marrow	Read-across

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

Ultra Repair Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

3-(trimethoxysilyl)propylamine

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOAEL	Carcinogenic toxicity study	43.8 mg/week	104 weeks (3 times/week)	Mouse (male/female)	No carcinogenic effect	Skin	Inconclusive, insufficient data

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

Ultra Repair Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

trimethoxyvinylsilane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	EPA OTS 798.4350	100 ppm	10 days (gestation, 6h/day)	Rat (female)	No effect		Experimental value
Maternal toxicity	NOAEL	EPA OTS 798.4350	25 ppm	10 days (gestation, 6h/day)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEL (P)	OECD 422	1000 mg/kg bw/day	≤ 43 day(s)	Rat (male)	No effect		Experimental value

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

7 / 12

Ultra Repair Adhesive

3-(trimethoxysilyl)propylamine

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	EPA OTS 798.4900	100 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect		Read-across
	LOAEL	EPA OTS 798.4900	600 mg/kg bw/day	14 days (gestation, daily)	Rat	Minor skeletal variations	Skeleton	Read-across
Maternal toxicity	NOAEL	Other	100 mg/kg bw/day	14 day(s)	Rat	No effect		Read-across
	LOAEL	Other	600 mg/kg bw/day	14 day(s)	Rat	Clinical signs; mortality; body weight; food consumption	General	Read-across
Effects on fertility	NOAEL	OECD 408	600 mg/kg bw/day	92 day(s)	Rat (male/female)	No effect		Read-across

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

Ultra Repair Adhesive

No (test) data on the mixture available

Chronic effects from short and long-term exposure

Ultra Repair Adhesive

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

Ultra Repair Adhesive

No (test) data on the mixture available

Judgement is based on the relevant ingredients

trimethoxyvinylsilane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		191 mg/l	96 h	Oncorhynchus mykiss		Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	EU Method C.2	168.7 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	EPA 67014-73-0	210 mg/l	7 day(s)	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC	OECD 211	28.1 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP

3-(trimethoxysilyl)propylamine

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 934 mg/l	96 h	Danio rerio	Semi-static system	Fresh water	Read-across; GLP
Acute toxicity crustacea	EC50	OECD 202	331 mg/l	48 h	Daphnia magna	Static system	Fresh water	Read-across; GLP
Toxicity algae and other aquatic plants	EC50	EU Method C.3	> 1000 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Read-across; GLP
Toxicity aquatic micro-organisms	EC50	Other	43 mg/l	5.75 h	Pseudomonas putida	Static system	Fresh water	Read-across; GLP

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

8 / 12

Ultra Repair Adhesive

trimethoxyvinylsilane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	51 %; GLP	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
	0.56 day(s)	500000 /cm ³	Calculated value

Half-life water (t1/2 water)

Method	Value	Primary degradation/mineralisation	Value determination
OECD 111: Hydrolysis as a function of pH	< 2.4 h; pH = 7	Primary degradation	Weight of evidence

3-(trimethoxysilyl)propylamine

Biodegradation water

Method	Value	Duration	Value determination
EU Method C.4	67 %; GLP	28 day(s)	Experimental value

Half-life water (t1/2 water)

Method	Value	Primary degradation/mineralisation	Value determination
	4 h; pH = 7	Primary degradation	QSAR

Conclusion

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

Ultra Repair Adhesive

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

trimethoxyvinylsilane

Log Kow

Method	Remark	Value	Temperature	Value determination
KOWWIN	Calculated	-2	20 °C	QSAR

3-(trimethoxysilyl)propylamine

Log Kow

Method	Remark	Value	Temperature	Value determination
		0.2	20 °C	QSAR

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

trimethoxyvinylsilane

(log) Koc

Parameter	Method	Value	Value determination
			Data waiving

Volatility (Henry's Law constant H)

Value	Method	Temperature	Remark	Value determination
8.72E-5 atm m ³ /mol		25 °C		Estimated value

Conclusion

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

Ultra Repair Adhesive

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

3-(trimethoxysilyl)propylamine

Groundwater

Groundwater pollutant

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

9 / 12

Ultra Repair Adhesive

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 10 (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants other than those mentioned in 08 04 09). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Recycle/reuse. Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber with energy recovery. Remove waste in accordance with local and/or national regulations. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 02 (plastic packaging).

SECTION 14: Transport information

Road (ADR), Rail (RID), Inland waterways (ADN), Sea (IMDG/IMSBC), Air (ICAO-TI/IATA-DGR)

14.1. UN number

Transport	Not subject
-----------	-------------

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Hazard identification number	
Class	
Classification code	

14.4. Packing group

Packing group	
Labels	

14.5. Environmental hazards

Environmentally hazardous substance mark	no
------------------------------------------	----

14.6. Special precautions for user

Special provisions	
Limited quantities	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Annex II of MARPOL 73/78	
--------------------------	--

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
6.99 % - 7.32 %	
73.60 g/l - 77.08 g/l	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
trimethoxyvinylsilane 3-(trimethoxysilyl)propylamine	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures,

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

10 / 12

Ultra Repair Adhesive

		<p>suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <p>a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";</p> <p>b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life-threatening lung damage";</p> <p>c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.</p> <p>6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.</p> <p>7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'</p>
trimethoxyvinylsilane	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	<p>1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:</p> <ul style="list-style-type: none"> — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:</p> <p>"For professional users only".</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>

National legislation Belgium

Ultra Repair Adhesive
No data available

National legislation The Netherlands

Ultra Repair Adhesive
Waterbezwaarlijkheid Z (1)

National legislation France

Ultra Repair Adhesive
No data available

National legislation Germany

Ultra Repair Adhesive
WGK 1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)

trimethoxyvinylsilane

TA-Luft 5.2.5

3-(trimethoxysilyl)propylamine

TA-Luft 5.2.5

National legislation United Kingdom

Ultra Repair Adhesive
No data available

Other relevant data

Ultra Repair Adhesive
No data available

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

3-(trimethoxysilyl)propylamine

A chemical safety assessment has been performed.

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

11 / 12

Ultra Repair Adhesive

SECTION 16: Other information

Full text of any H-statements referred to under heading 3:

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H373 May cause damage to organs (bladder) through prolonged or repeated exposure if swallowed.

(*)	INTERNAL CLASSIFICATION BY BIG
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet has been elaborated for use within the European Union, Switzerland, Iceland, Norway and Lichtenstein. It may be consulted in other countries, where local legislation with regards to the set-up of safety data sheets will take precedence. It is your obligation to verify and apply such local legislation. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2;3

Publication date: 2011-07-19

Date of revision: 2017-09-26

Revision number: 0600

Product number: 51334

12 / 12