Technical Data Sheet

Universal Woodworm & Dry Rot Killer+

Solvent Based Treatment for Exterior Use





Description:

Universal Woodworm & Dry Rot Killer+ is a solvent-borne product based on low viscosity linseed oil. It contains active ingredients effective against wood-destroying fungi, wood-discolouring fungi (blue stain) and wood boring insects.

Universal Woodworm & Dry Rot Killer+ penetrates easily into wood and thereby gets deep into inner layers. It is moisture regulating and provides an adhesive surface for subsequent finishing paints (top coats). After drying, the product is odourless.

Universal Woodworm & Dry Rot Killer+ carries the HSE Approval No 10038.

ALL BATS ARE PROTECTED UNDER THE WILDLIFE AND COUNTRYSIDE ACT 1981, BEFORE TREATING ANY STRUCTURE USED BY BATS, CONSULT ENGLISH NATURE, SCOTTISH NATURAL HERITAGE OR THE COUNTRYSIDE COUNCIL FOR WALES.

Product Uses:

Universal Woodworm & Dry Rot Killer+ is a wood preservative used for pre-treatment of non-resistant wood in outdoor use.

For use on all outside wood, that is not in direct contact to soil or water surface and not stressed statically. This includes facades, carports, shutters and balcony railings.

Active Ingredients:

Permethrin 0.06% w/w: A commonly used pyrethroid insecticide which has excellent efficacy against a wide range of wood boring insects.

Propiconazole 0.6% w/w: A Triazole Fungicide which has excellent efficacy against a range of wood destroying fungi.

IPBC (3-lodo-2-Propynyl Butyl Carbamate) 0.3% w/w: A Carbamate Fungicide which is added to improve the efficacy envelope even further providing excellent efficacy against a range of wood staining fungi.

Preparation:

The wood surface must be clean and dry before treatment. All existing coatings must be completely removed. If necessary, all grey and deteriorated wood should be sanded down to a clean sound surface. The wood must be frost-free when treated.

Application:

Universal Woodworm & Dry Rot Killer+ is a ready to use product and should not be diluted. Shake the container vigorously to ensure contents are thoroughly mixed.

The product should be applied evenly in order to get the best results. Re-seal the container after use.

Coverage:

This is greatly dependant on the type of timber being treated, but as a rough guide coverage will be effective at 160ml/m².

Cleaning:

Brushes etc. can be cleaned with White Spirit followed by detergent.

Storage Conditions:

Containers should be stored out of direct sunlight in dry conditions away from sources of ignition. They should be stored undercover below a temperature of 30°C.

Packaging:

5L and 25L Containers.

Product of: Cromar Building Products

Date: May 2018