


SLIM 52" Ceiling Fan
FR-W2003-52L

MODERN FORMS
SMART FANS



PRODUCT DESCRIPTION

This sleek and sculptural design acts as a functional vanguard in minimalist and transitional modern spaces. Running on stealth mode, the DC motor ensures silent operation of this powerful smart fan, while the Breeze Mode feature mimics the natural outside breeze - indoors. The classic stainless steel look of Slim will enhance any trendy restaurant or residential kitchen looking to maintain a streamlined look to their space.

SPECIFICATIONS

- Construction:** Aluminum
- Blade:** 14° Pitch, 52" sweep, ABS
- Downrod:** 3/4"W X 4.5"H included
- Mounting Slope:** Up to 30°
- Wire:** 80"
- Hanging Weight:** 19 lbs
- Total Power:** 49W
- Standards:** UL/cUL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional luminaire cover included
- Includes remote control with wall cradle
- Wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

LUMINAIRE PERFORMANCE

- Light Source:** LED
- Light Wattage:** 13W
- Dimming:** Integrated
- Color Temperature:** 3000K
- Rated Life:** 50,000 Hours
- Standards:** Title 24 JA8-2016 Compliant, Title 20 Compliant, Energy Star
- Motor:** 125 x 12 sensorless DC motor

AIRFLOW/ENERGY EFFICIENCY

- Weighted-Average Air flow CFM:** 4158(weighted-average)/6142(high)
- Energy Use (W) :** 16(weighted-average)/19(high)
- Estimated Yearly Energy Cost (\$):** 5(weighted-average)
- Efficiency (CFM/W):** 181(weighted-average)/256(high)

ORDER NUMBER

Model	LED Lumens	Delivered Lumens	Housing	Blade
FR-W2003-52L	1100	376	MB <i>Matte Black</i>	MB <i>Matte Black</i>
			MW <i>Matte White</i>	MW <i>Matte White</i>
			AL <i>Brushed Aluminum</i>	TT <i>Titanium Silver</i>

Example: **FR-W2003-52L-MB**

For 2700K add "-27"; 3500K add "-35" before the finish: **FR-W2003-52L-27-MW**

*Results may vary based on application and surroundings.



modernforms.com
Phone (866) 810.6615
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050







Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

SLIM 52" Ceiling Fan
FR-W2003-52L

MODERN FORMS
SMART FANS

OPTIONAL ACCESSORIES

Bluetooth Wall Control		F-WCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control		F-RCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Wi-Fi Touch Panel Wall Control		F-TS	BK Black WT White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
Downrod		XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in	AS Automotive Silver BA Brushed Aluminum BZ Bronze CFI Carbon Fiber** DW Dark Walnut GB Gloss Black GH Graphite GW Gloss White KO Koa† MB Matte Black Matte MW White OB Oil Rubbed Bronze SS Stainless Steel TT Titanium Silver	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		XF-I		Connects two downrods together.
Sloped Ceiling Kit		XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control - **F-WCBT-WT**, Remote Control - **F-RCBT-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope Pitch	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

†Koa downrods available in 12", 18", 24" and 36"

modernforms.com
Phone (866) 810.6615
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760