
# quorum



# Windmill 52-in Galvanized Indoor/ Outdoor Ceiling Fan (10-Blade)

195210-9



#### **FAN HEIGHT**

Using 6" Downrod

• Distance of 16.5" ODistance of 11.5"

#### **GENERAL SPECS**

3 Finishes Available Lifetime Motor Warranty Ten ABS Blades 52" Blade Sweep 30-Degree Blade Pitch 80" Lead Wire

6" Downrod Included ETL Damp Listed

### MECHANICAL SPECS

DC-165M Motor

6 Speeds-Reversible w/ Wall Control 6 Poles

.33/.22/.16/.09/.06/.04 AMPS on H/M/L 26/17/12/9/5/3 WATTS on H/M/L

84/74/62/51/41/30 RPMS on H/M/L

Light Kit Adaptable Remote Control Included

Not Hugger Adaptable

Not Slope Ceiling Kit Adaptable

Maximum 25° Slope with Minimum 18" Downrod

Maximum Length Optional Downrod 48"

#### **ENERGY SPECS**

Energy Information at High Speed Airflow: 2445 Cubic Feet/Minute Electricity Use: 20 Watts (Excludes Lights) Airflow Efficiency: 122 Cubic Feet/Minute/Watt Visit QuorumInternational.com for DOE Energy Guide

## REMOTE CONTROL



Included

#### **INSTALLATION NOTE**

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

#### LIGHT KIT OPTIONS

Additional Light Kit options on page 232