
quorum



Windmill 44-in Oiled Bronze Indoor/ Outdoor Ceiling Fan (10-Blade)

194410-86



FAN HEIGHT

Using 6" Downrod

• Distance of 16.5"

ODistance of 11.5"

GENERAL SPECS

2 Finishes Available Lifetime Motor Warranty Ten Aluminum Blades 44" Blade Sweep 30-Degree Blade Pitch 80" Lead Wire 6" Downrod Included

ETL Damp Listed

MECHANICAL SPECS

DC-125 Motor

6 Speeds-Reversible w/ Wall Control

8 Poles

.39/.29/.20/.13/.11/.05 AMPS on H/M/L

32/22/15/10/7/3 WATTS on H/M/L

100/90/80/70/60/50 RPMS on H/M/L

Wall Control Included w/ 194410-9 only Light Kit Adaptable

Remote Control Included w/ 194410-86 only

Not Hugger Adaptable

Not Slope Ceiling Kit Adaptable

Maximum 25° Slope with Minimum 18" Downrod

Maximum Length Optional Downrod 48"

ENERGY SPECS

Energy Information at High Speed Airflow: 2296 Cubic Feet/Minute Electricity Use: 17 Watts (Excludes Lights) Airflow Efficiency: 135 Cubic Feet/Minute/Watt Visit QuorumInternational.com for DOE Energy Guide

REMOTE CONTROL



Included

INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

LIGHT KIT OPTIONS

Additional Light Kit options on page 232