


CLEAN

F-003L

52" Ceiling Fan

WAC SMART FANS



PRODUCT DESCRIPTION

A smart fan with minimalist appeal. It perfectly suits a range of design styles without overpowering. Convenient wall and remote control options provide flexibility and ease of use, while a whisper-quiet and energy-efficient DC motor powers the ABS blades.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Includes remote control with wall cradle (RC20-WT)
- Wall control for 3, 4-way control sold separately
- Compatible with WAC Smart Fans app

AIRFLOW/ENERGY EFFICIENCY

Weighed-Average Airflow CFM:	4039/5924
Energy Use (W):	21/29
Estimated Yearly Energy Cost (\$):	6
Efficiency (CFM/W):	188
Max RPM:	160

ORDER NUMBER

Model	Housing	Blade
F-003L	BA <i>Brushed Aluminum</i>	TT <i>Titanium Silver</i>
	MB <i>Matte Black Matte</i>	MB <i>Matte Black</i>
	MW <i>White</i>	MW <i>Matte White</i>
	SB <i>Soft Brass</i>	MW <i>Matte White</i>

F-003L-__

Example: F-003L-MW

*This fan comes uni-pack - blade select options are not available

*Range results may vary based on application and surroundings.



The WAC app synchronizes seamlessly with smart home devices you already own



wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

WAC retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUL 2020

SPECIFICATIONS

Construction:	Aluminum, ABS
Blade:	20° Pitch, 52" sweep
Downrod:	3/4"W X 4.5"H included
Mounting Slope:	Up to 30°
Wire:	80"
Hanging Weight:	17 lbs
Total Power:	45W
Standards:	UL/cUL Wet Location listed, Energy Star Rated, Title 24 JA8-2016, Title 20 Compliant
Motor Type:	120 x 15 sensorless DC motor

WIRELESS PERFORMANCE

Wi-Fi Range:	Up to 150 ft*
Bluetooth Range:	Up to 150 ft*

LUMINAIRE PERFORMANCE

Light Source:	LED
Light Wattage:	13W
Lumens/Delivered Lumens:	1110/750
Dimming:	Integrated
CRI:	90
Color Temperature:	3000K
Rated Life:	50,000 hours

CLEAN





F-003L

52" Ceiling Fan

WAC

SMART FANS

OPTIONAL ACCESSORIES

Bluetooth Wall Control		WC20-	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control		RC20-	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		DR12- 12IN DR18- 18IN DR24- 24IN DR36- 36IN DR48- 48IN DR60- 60IN DR72- 72IN		All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		DC-	BA Brushed Aluminum MB Matte Black MW Matte White SB Soft Brass	Connects two downrods together.
Sloped Ceiling Kit		SC-		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control - **WC20-WT**, Remote Control - **RC20-WT**, Downrod - **DR12-BN**, Downrod Coupler - **DC-MB**, Sloped Ceiling Kit - **SC-MW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13o	14-17o	18-21o	22-25o	26-29o	30-32o	33-35o	36-38o	39-41o	42-44o	45o
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire