





PRODUCT DESCRIPTION

Intelligent minimalism combined with a sleek form and substantial function. Zelda by WAC is a tri-blade phenomenon that cools your home while illuminating the space with the best technology in the world. Pair with the WAC Smart Fans app for additional functionality.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- · Luminaire cover not included
- Includes remote control with wall cradle (RC20-WT)
- · Wall control for 3, 4-way control sold separately
- Compatible with WAC Smart Fans app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 3797/5801 Weighted-Average/High Energy Use (W): 18/24 Estimated Yearly Energy Cost (\$): Weighted-Average/High Efficiency (CFM/W): 207 Max RPM: 151

ORDER NUMBER

| Model | Housi | ng | Blade | | | | |
|--------|-------|----------------|-------|-------------|--|--|--|
| F-088L | BN | Brushed Nickel | МВ | Matte Black | | | |
| F-000L | SB | Soft Brass | МВ | Matte Black | | | |

F-088L-

Example: F-088L-SB/MB

*This fan comes uni-pack - blade select options are not available

* Range results may vary based on application and surroundings.

SPECIFICATIONS

Construction: Steel, ABS

Blade: 14° Pitch, 60" sweep Downrod: 3/4"W X 4.5"H included

Mounting Slope: Up to 30° Wire: 80"

Hanging Weight: 17 lbs 44W **Total Power:**

Standards: UL/cUL Damp Location listed, Title 24

JA8-2016, Title 20, Energy Star

Motor Type: DC 125 x 20

WIRELESS PERFORMANCE

Wi-Fi Range: Up to 150 ft* Up to 150 ft* **Bluetooth Range:**

LUMINAIRE PERFORMANCE

LED **Light Source: Light Wattage:** 19.5W Lumens/Delivered: 1600/763 Dimming: Integrated CRI: 90 **Color Temperature: Rated** 3000K Life: 50,000 hours

The WAC app synchronizes seamlessly with smart home devices you already own













waclighting.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760



OPTIONAL ACCESSORIES

| OPTIONAL ACCESSORIES | | | | | |
|--------------------------|-------|--|----------|------------------------------|--|
| Bluetooth Wall Control | | WC20- | WT | White | Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control. |
| Bluetooth Remote Control | A B V | RC20- | wt | White | Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries. |
| Downrod | | DR12- 12IN DR18- 18IN DR24- 24IN DR36- 36IN DR48- 48IN DR60- 60IN DR72- 72IN | | | All our downrods are .75" I.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field. |
| Downrod Couplers | | DC- | BN SB | Brushed Nickel Soft Brass | Connects two downrods together. |
| Sloped Ceiling Kit | | SC- | | | Designed to accommodate buildings with steeper sloped ceilings up to 450 or 12/12 pitch. |

Examples: Wall Control - WC20-WT, Remote Control - RC20-WT, Downrod - DR12-BN, Downrod Coupler - DC-SB, Sloped Ceiling Kit - SC-BN

SUGGESTED DOWNROD HEIGHT USAGE

| Ceiling Height | 15' | 14' | 13' | 12' | 11' | 10' | 9' |
|----------------|-----|-----|-----|-----|-----|-----|-----|
| Downrod | 72" | 60" | 48" | 36" | 24" | 18" | 12" |

SLOPED CEILING DEGREE CONVERSION CHART

| Degree | 4-8° | 9-130 | 14-17o | 18-21o | 22-25o | 26-290 | 30-320 | 33-350 | 36-380 | 39-41o | 42-440 | 450 |
|---------------|-------|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------|
| Ceiling Slope | 1/12 | 2/12 | 3/12 | 4/12 | 5/12 | 6/12 | 7/12 | 8/12 | 9/12 | 10/12 | 11/12 | 12/12 |
| Pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch |

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire