



PRODUCT DESCRIPTION	SPECIFICATIONS	
Transitional style meets smart technology with this versatile smart fan	Construction: Aluminum	
available in four weather-resistant finishes as well as a 316 marine-	Blade: 13° Pitch, 42" sweep, ABS	
grade stainless steel for harsh outdoor climates. The 42 inches is ideal for bedrooms, patios and breakfast nooks while the 52 inches works	Downrod: 1" O.D. x 4.5"H included	
great in living rooms and medium-sized spaces. The LED luminaire,	Mounting Slope: Up to 30°	
powered by WAC, takes this design from beautiful to brilliant. Connect	Lead Wire: 80"	
with our exclusive Modern Forms app for even more life	Hanging Weight: 15.5 lbs	
enhancements.	Total Power: 44.5W	
	Standards: ETL/cETL Wet Location listed	
FEATURES	LIGHT KIT PERFORMANCE	
 6 fan speeds through both Summer and Winter Modes 	Light Source: LED	
Silent DC motor	Light Wattage: 19.5W	

- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Optional RF remote control with wall cradle sold separately
- Compatible with Modern Forms app

ESTIMATED AIR PERFORMANCE

Airflow: 4722 cubic ft per minute on high Power: 25 watts on high Airflow Efficiency: 192 cubic ft per minute per watt Revolutions Per Minute: 210 RPMs on high

ORDER NUMBER

Model	LED Lumens	Delivered Lumens	_	Housing		Blade	
FR-W1801-42L	1600	846	BZ GH MW SS	Bronze Graphite Matte White Stainless Steel	WG	Bronze Weathered Gray Matte White Steel Gray	

Example: FR-W1801-42L-GH/MW

For 2700K add "-27"; 3500K add "-35" before the finish: FR-W1801-42L-27-BZ

*Results may vary based on application and surroundings.



Works with SmartThings

modernforms.com Phone (866) 810.6615 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

Modern Forms retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2019

Light Wattage: 19.5W Dimming: Integrated Color Temperature: 3000K (2700K / 3500K options available) Rated Life: 50,000 Hours Standards: Title 24 JA8-2016 Compliant

WIRELESS PERFORMANCE

RF Pairing Distance: Up to 30 ft from fan **Wi-Fi Range:** Up to 150 ft*

WYND 42" Ceiling Fan

MODERN FORMS SMART FANS

FR-W1801-42L

OPTIONAL ACCESSORIES					
RF Wall Control	F-WC		wt	White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
RF Remote Control	F-RC		wт	White	Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.
Wi-Fi Touch Panel Wall Control	F-TS		ВК WT	Black White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
Downrod	XF-12 XF-18 XF-24 XF-36 XF-48 XF-60 XF-72	12in 18in 24in 36in 48in 60in 72in	AS BA BZ CFI DW	Automotive Silver Brushed Aluminum Bronze Carbon Fiber** Dark Walnut	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers	XF-I		GB GH GW KO	Gloss Black Graphite Gloss White Koat	Connects two downrods together.
Sloped Ceiling Kit	XF-SCK		MB MW OB SS TT	Matte Black Matte White Oil Rubbed Bronze Stainless Steel Titanium Silver	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - F-WC-WT, RF Remote Control - F-RC-WT, Wi-Fi Touch Panel - F-TS-WT, Downrod - XF-12-BZ, Downrod Coupler - XF-I-BZ, Sloped Ceiling Kit - XF-SCK-DW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9′		
Downrod	72″	60″	48″	36″	24″	18″	12″		
SLOPED CEILING DEGREE CONVERSION CHART									

SLOPED CLIEING DEGREE CONVERSION CHART												
Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire **Carbon Fiber downrods available in 12", 18", 24" and 36"

*Koa downrods available in 12", 18", 24" and 36"

modernforms.com	Headquarters/Eastern Distribution Center	Central Distribution Center	Western Distribution Center
Phone (866) 810.6615	44 Harbor Park Drive	1600 Distribution Ct	1750 Archibald Avenue
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Ontario, CA 91760