


WYND 52" Ceiling Fan
FR-W1801-52L

MODERN FORMS
SMART FANS



PRODUCT DESCRIPTION

Transitional style meets smart technology with this versatile smart fan available in four weather-resistant finishes as well as a 316 marine-grade stainless steel for harsh outdoor climates. The 42 inches is ideal for bedrooms, patios and breakfast nooks while the 52 inches works great in living rooms and medium-sized spaces. The LED luminaire, powered by WAC, takes this design from beautiful to brilliant. Connect with our exclusive Modern Forms app for even more life enhancements.

SPECIFICATIONS

- Construction:** Aluminum
- Blade:** 13° Pitch, 52" sweep, ABS
- Downrod:** 1" O.D. x 4.5"H included
- Mounting Slope:** Up to 30°
- Lead Wire:** 80"
- Hanging Weight:** 17.5 lbs
- Total Power:** 54.5W
- Standards:** ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Optional RF remote control with wall cradle sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

- Light Source:** LED
- Light Wattage:** 19.5W
- Dimming:** Integrated
- Color Temperature:** 3000K (2700K / 3500K options available)
- Rated Life:** 50,000 Hours
- Standards:** Title 24 JA8-2016 Compliant

ESTIMATED AIR PERFORMANCE

- Airflow:** 6568 cubic ft per minute on high
- Power:** 35 watts on high
- Airflow Efficiency:** 188 cubic ft per minute per watt
- Revolutions Per Minute:** 168 RPMs on high

WIRELESS PERFORMANCE

- RF Pairing Distance:** Up to 30 ft from fan
- Wi-Fi Range:** Up to 150 ft*

ORDER NUMBER

Model	LED Lumens	Delivered Lumens	Housing	Blade
FR-W1801-52L	1600	846	BZ <i>Bronze</i>	<i>Bronze</i>
			GH <i>Graphite</i>	WG <i>Weathered Gray</i>
			MW <i>Matte White</i>	<i>Matte White</i>
			SS <i>Stainless Steel</i>	<i>Steel Gray</i>

Example: **FR-W1801-52L-GH/MW**

For 2700K add "-27"; 3500K add "-35" before the finish: **FR-W1801-52L-27-BZ**

*Results may vary based on application and surroundings.



modernforms.com
Phone (866) 810.6615
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122







Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

WYND 52" Ceiling Fan

FR-W1801-52L

MODERN FORMS SMART FANS

OPTIONAL ACCESSORIES

RF Wall Control		F-WC	WT White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
RF Remote Control		F-RC	WT White	Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.
Wi-Fi Touch Panel Wall Control		F-TS	BK Black WT White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
Downrod		XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in	AS Automotive Silver BA Brushed Aluminum BZ Bronze CFI Carbon Fiber** DW Dark Walnut GB Gloss Black GH Graphite GW Gloss White KO Koa† MB Matte Black Matte MW White OB Oil Rubbed Bronze SS Stainless Steel TT Titanium Silver	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		XF-I		Connects two downrods together.
Sloped Ceiling Kit		XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - **F-WC-WT**, RF Remote Control - **F-RC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope Pitch	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

†Koa downrods available in 12", 18", 24" and 36"

modernforms.com
Phone (866) 810.6615
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760