
ZEPHYR 5

FR-W2401-62L

62" Ceiling Fan

MODERN FORMS



PRODUCT DESCRIPTION

With smart controls and a discreet DC Motor, Zephyr 5 is a form of luxury that comes in a stylish three blade design. A robust LED luminaire with artisan-crafted opal glass and thick aerodynamically soundless blades round out the design. Available in four rich architectural finishes. The Modern Forms app allows for full control of one or many smart fans and integration with current smart home control systems.

FEATURES

- · 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- Optional LED luminaire cover included
- Includes BT remote control
- Optional wall control sold separately
- · Compatible with Modern Forms app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 5220/7307 Weighted-Average/High Energy Use (W): 25/34 7 Estimated Yearly Energy Cost (\$): Weighted-Average/High Efficiency (CFM/W): 210 Max RPM: 123

ORDER NUMBER

Model	Hous	ing	Blade				
FR-W2401-62L	GH	Graphite	WW	Weathered Wood			
	MB	Matte Black	DK	Distressed Koa			
	MB	Matte Black	MB	Matte Black			
	MW	Matte White	MW	Matte White			

Example: FR-W2401-62L-MW

SPECIFICATIONS

Construction: Aluminum, ABS Blade: 16° Pitch, 62" sweep 3/4"W + 8"H included Downrod:

Mounting Slope: Up to 30° Wire: 80" 17 lbs **Hanging Weight: Total Power:** 54W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20, Energy Star rated

Motor Type: 120 x 25 sensorless DC motor

WIRELESS PERFORMANCE

Up to 150 ft* Wi-Fi Range: **Bluetooth Range:** Up to 150 ft

LUMINAIRE PERFORMANCE

Light Source: I FD **Light Wattage:** 20W Lumens/Delivered Lumens: 1600/846 Dimming: Integrated CRI:

CCT Color Temperature: 3000K (2700K/4000K/5000K) selectable

Rated Life: 50,000 hours

*Results may vary based on application and surroundings.

*This fan comes uni-pack - blade select options are not available

The Modern Forms app synchronizes seamlessly with smart home devices you already own













modernforms.com Phone (800) 526.2588 (800) 526.2585 Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

62" Ceiling Fan



OPTIONAL ACCESSORIES

OPTIONAL ACCESSORIES				
Bluetooth Wall Control		F-WCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	**************************************	F-RCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Moder Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN		All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		XF-I		Connects two downrods together.
Sloped Ceiling Kit		XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control: F-WCBT-WT, Remote Control: F-RCBT-WT, Downrod: XF-12-BN, Downrod Coupler: XF-I-MB, Sloped Ceiling Kit: XF-SCK-MW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45° .

NOTE: Recommended maximum downrod length of 72" with 80" lead wire