
ULTRA GERMICIDAL SMART FAN

54" Ceiling Fan









Create a sanctuary with a groundbreaking fan system incorporating Ultraviolet-C (UV-C) light. Using a patent-pending system, which combines a UV-C LED ring with a powerful fan, the Ultra Germicidal Smart Fan can substantially decrease the concentration of viral pathogens, including the SARS-CoV-2 virus, in the air.** Third-party lab tests have shown a 99.99% reduction of collectable active pathogen in the air and that the active SARS-CoV-2 virus was not detectable in the breathable air after 30 minutes of operation of the Ultra Germicidal Smart Fan in a 8'x8'x10' test room.**

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Includes BT remote control
- Compatible with Modern Forms app
- Includes violet LED indicators to let you know the UV-C module is on

ORDER NUMBER


| Model | Housing | | | Blade | | | | |
|--------------|---------|----------------|----|-------------|--|--|--|--|
| FR-D2102-54U | BN | Brushed Nickel | MB | Matte Black | | | | |
| | MB | Matte Black | MB | Matte Black | | | | |
| | MW | Matte White | MW | Matte White | | | | |

Example: FR-D2102-54U-MW

*Reduces the SARS COV-2 viruses and other airborne pathogens.

**Based on tests conducted by an independent CAP and CLIA accredited lab, Innovative Bioanalysis. The report is available at modernforms.com/ultra. The effectiveness of the Ultra Smart Fan will vary based upon application and surroundings, including but not limited to room dimensions and airflow.

WARNING: This product emits ultraviolet (UV) radiation. Exposure to UV radiation can cause serious personal injuries, including damage to eyes and skin. Avoid direct exposure to the UV light. Do not operate the product while anyone could be directly exposed to the UV light. For more safety instructions, please refer to page 5 of the fan's instruction manual ("UV Safety Rules").



SPECIFICATIONS

Construction: Aluminum, ABS

17° Pitch, 54" sweep Blade:

3/4"W X 10"H + 3/4"W + 6"H included **Downrods:**

Mounting Slope: Up to 30°

Wire: 80" **Hanging Weight:** 18 lbs **Total Power:**

Standards: UL/cUL Damp Location listed, Title 24 JA8-2016

Compliant, Title 20, Energy Star rated

120 x 20 sensorless DC motor **Motor Type:**

This fan comes uni-pack - blade select options are not available

WIRELESS PERFORMANCE

Wi-Fi Range: Up to 150 ft (Results may vary based on application and surroundings) **Bluetooth Range:** Up to 150 ft (Results may vary based on application and surroundings)

UV-C LED PERFORMANCE

Light Source: UV-C LED Modules (only operate when fan is spinning)

Light Wattage: 16.5W Dimming: N/A Peak wavelength: 275 nm

Your module will flash when it has Maintenance:

80-hours left of life.

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 3278/5172 (tested with 10-inch

Weighted-Average/High Energy Use (W): 20/26 Estimated Yearly Energy Cost (\$): 5 Weighted-Average/High Efficiency (CFM/W): 168 Max RPM: 169

The Modern Forms app synchronizes seamlessly with smart home devices you already own













Disclaimer: While there may be information on our website relating to the Ultra Germicidal Smart Fan's effectiveness in reducing SARS-CoV-2 and other pathogens in the air, Modern Forms makes no claims that its products can cure, treat or prevent any conditions, including COVID-19 or other conditions that may be caused by airborne pathogens. Always consult your healthcare provider with any health-related questions.

waclighting.com Phone (800) 526.2588 (800) 526.2585 44 Harbor Park Drive Port Washington, NY 11050

Headquarters/Eastern Distribution Center Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

ULTRA GERMICIDAL SMART FAN

FR-D2102-54U 54" Ceiling Fan



MODERN FORMS SMART FANS

OPTIONAL ACCESSORIES

| Bluetooth Remote Control | F-RCUV- | WT White | Control fan speed and UV light, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries. |
|--------------------------|--|-----------------|---|
| Downrod | XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN | | All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field. |
| Downrod Couplers | XF-I | | Connects two downrods together. |
| Sloped Ceiling Kit | XF-SCK | | Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch. |

Examples: Remote Control: F-RCUV-WT, Downrod: XF-12-BN, Downrod Coupler: XF-I-MB, Sloped Ceiling Kit: XF-SCK-MW

SUGGESTED DOWNROD HEIGHT USAGE

| Ceiling Height | 15' | 14' | 13' | 12' | 11' | 10' | 9' |
|----------------|-----|-----|-----|-----|-----|-----|-----|
| Downrod | 72" | 60" | 48" | 36" | 24" | 18" | 12" |

SLOPED CEILING DEGREE CONVERSION CHART

| Degree | 4-8° | 9-13° | 14-17° | 18-21° | 22-25° | 26-29° | 30-32° | 33-35° | 36-38° | 39-41° | 42-44° | 45° |
|---------------|-------|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------|
| Ceiling Slope | 1/12 | 2/12 | 3/12 | 4/12 | 5/12 | 6/12 | 7/12 | 8/12 | 9/12 | 10/12 | 11/12 | 12/12 |
| Pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch |

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

Disclaimer: While there may be information on our website relating to the Ultra Germicidal Smart Fan's effectiveness in reducing SARS-CoV-2 and other pathogens in the air, Modern Forms makes no claims that its products can cure, treat or prevent any conditions, including COVID-19 or other conditions that may be caused by airborne pathogens. Always consult your healthcare provider with any health-related questions.