



The pump is a submersible drainage pump fitted with cast iron vortex style impeller. The pump can handle particles up to 15mm.

**The pump is characterised by:**

- Cast iron pump body and impeller for durability
- Fully automatic operation.
- Triple seal system: Dual Mechanical Seal (carbon/ceramic) and oil seal
- Carry handle.
- Versatile outlet connection.
- 240V single phase motor with in-built thermal protection
- thermal overload.
- 10m of power cable.
- Dewatering of cellars, etc.
- Pumping clean or slightly dirty water
- Flows to 133 L/min
  - Heads to 7.0 m

**Liquid:**

Clean water temperature range: 2 – 35 °C

**Materials:**

Pump body: Cast Iron  
 Impeller: Cast iron/Nylon  
 Shaft: Stainless Steel  
 Shaft seal: Dual mechanical seal (carbon/ceramic)

**Installation:**

Maximum ambient temperature: 40 °C  
 Pipe connections discharge: 1.1/4" F

**Electrical data:**

Rated voltage: 240V  
 Mains frequency: 50 Hz  
 Rated output: 180W  
 Current: 1.6 amps  
 Capacitor: 8 uF  
 Motor duty: Continuous  
 Motor type: Asynchronous  
 Motor protection: In-built thermal overload  
 Ingress protection: IP 68  
 Insulation class: B  
 Power cable length: 10 m H07RNF  
 Net weight: 9.3 kg

**2 Year Bianco Pumpz Warranty**

**BULK QUANTITY APPLIES TO THIS PRODUCT**

