


Description

LED Commercial downlight has an innovative separable design for commercial applications, combining the latest in LED technology 95-100lm/w brightness, 50,000hrs high efficient dim LED driver, beautiful light distribution optic lens and variable size trim & light source engine for recessed J-box ceiling installation, for 80% energy-saving, ideal for replacing 60W-400W halogen, CFL

Features

- * Silver aluminum housing & milky lens
- * **1-10VDC dimming** UL driver
- * Bridgelux SMD LED source
- * Easy installation and operation
- * CRI >80Ra, THD <15%
- * CCT 3000K/3500K/4000K/5000K or CCT tunable
- * Working temperature: -30°C~ 45°C
- * Eco friendly without mercury
- * Instant start, no flickering, no humming
- * Energy saving, long lifespan
- * No UV or IR
- * 5 years warranty
- * Damp IP44 rated




6" 8" LED Commercial Downlight




Specification

Product number	Watts adjustable	Voltage	Cut-off size	Dimension(B*A)	LED chips	Dimmable	IP rating	Certificates	Equivalent
CH-CE6-40W	18W/27W/40W	AC 100-277V	6"-6.7"	Φ7.45*7.68"	Bridgelux SMD	1-10v dim DVTV(LUTRON) IP710(LEVITON)	IP44 (damp rated)	UL cUL Energy Star	60-200W CFL
CH-CE6-80W	50W/65W/80W			Φ7.45*10.05"					250-400W CFL
CH-CE8-40W	18W/27W/40W		7.7"-8.4"	Φ9.26*8.2"					60-200W CFL
CH-CE8-80W	50W/65W/80W		Φ9.26*10.56"	250-400W CFL					

Photometrics



Illuminance curve



Application

Shopping center mall or other commercial indoor recessed ceiling areas, like conference room, office, livingroom etc.

