





# **PRODUCT FEATURES:**

- Optical design, greatly improved the light utilization and evenness
- ❖ High efficiency LED Driver, voltage AC120-277;

**WALL PACK LIGHT** 

- $\diamond$  Cast Aluminum design, better cooling, light quality, LED Tj <  $85^{\circ}$ C.
- Photocell Control (Optional)

MODEL #	
PROJECT:	
NOTES:	
DATE:	
PREPARED BY:	

# **Additional Information:**

Power: 70W

o Input: AC 120-277V

o Light Source: LUMILEDS

o Driver: NOVBO POWER





















# **PRODUCT APPLICATIONS:**

The WALL PACK LED Lighting Series can be widely used for Indoor or Outdoor (Wet Location) Excellent for Museums, Art Galleries, Shopping Malls, Office Buildings, Walls and many other applications









# **Structure Features:**

Shell Materials: Aluminum & PC

Finish: Dark Bronze/White

Net Weight: 1.5KG (3.3 LBS)

Product Size: 211mm\*181mm\*103mm

Carton Size: 525mm\*390mm\*370mm





# **WALL PACK LIGHT**


# **TECHNICAL PARAMETERS:**

Туре	70WAWP27-XXK-Z						
Power	70W	Lighting Angle	74*92°				
Input Voltage	AC120-277V	LED Brightness Decay	<5%/6000 hrs				
PF	>0.99	Working Life	>75000 hrs				
Driver Efficiency	>90%	Working Temperature	-30 - +45℃				
Luminous Flux	9841 Lm	Storage Temperature	-40 -+80℃				
Color Temperature	4000K/5000K	Protection Level Wet Location					
CRI	Ra>70	Cable	Input Connect, No Cable				

### **PHOTOMETRY:**







# ORDERING EXAMPLE:70WAWP27-XXK-Z-P

WSD	70W	AWP	27	ххк	Z	P
Company	Power	Product	Voltage	ColorTemp	FINISH	Control
WSD LED INC	<b>45W</b> (45W) <b>70W</b> (70W)	<b>AWP</b> Wall Pack	<b>27</b> AC120-277V	<b>50K</b> (4000K) <b>50K</b> (5000K) <b>± 500K</b>	<b>D</b> Dark Bronze <b>W</b> White	<b>P</b> Photocell